


USE TYPEWRITER OR BALL
POINT PEN—PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment—Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Sedgwick	Fraction NW 1/4 SE 1/4 NW 1/4	Section number 26	Township number T 27 S R 1	Range number NW	
2. Distance and direction from nearest town or city: 1/4 Mi. S. of Maple St. & 300' W. of I-235 Street address of well location if in city:			3. Owner of well: Utility Contractors, Inc. R.R. or street: 659 N. Market City, state, zip code: Wichita, Kansas			
4. Locate with "X" in section below: N W E S 1 Mile		Sketch map: 		6. Bore hole dia. <u>30</u> in. Completion date <u>11-23-79</u> Well depth <u>55</u> ft.		
5. Type and color of material		From		To		7. ☐ Coble tool ☐ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☒ Reverse rotary
						8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☒ Other
						9. Casing: Material <u>steel</u> Weight: Above <u>16</u> in. below <u>16</u> in. Threaded ☐ Welded ☒ Surface <u>36</u> in. RMP ☐ PVC ☐ Weight <u>31.75</u> lbs./ft. Dia. <u>16</u> in. to <u>16</u> ft. depth Wall Thickness: inches or Dia. <u>16</u> in. to <u>16</u> ft. depth gauge No. <u>188</u>
						10. Screen: Manufacturer's name <u>DOVER</u> Type <u>steel</u> Dia. <u>16</u> " Slot/gauze <u>1/8</u> Length <u>40</u> ' Set between <u>15</u> ft. and <u>55</u> ft. Gravel pack? <u>yes</u> Size range of material <u>1/8 & 1/2</u>
						11. Static water level: <u>10</u> ft. below land surface Date <u>11-23-79</u> mo./day/yr.
(Use a second sheet if needed)						12. Pumping level below land surfaces: ____ ft. after ____ hrs. pumping ____ g.p.m. ____ ft. after ____ hrs. pumping ____ g.p.m. Estimated maximum yield <u>1000</u> g.p.m.
						13. Water sample submitted: ____ mo./day/yr. Yes ☒ No ☐ Date ____
						14. Well head completion: ☐ Pitless adapter <u>36</u> inches above grade
						15. Well grouted? <u>yes</u> With: ☒ Neat cement ☒ Bentonite ☐ Concrete Depth: From <u>0</u> ft. to <u>10</u> ft.
						16. Nearest source of possible contamination: <u>Flood</u> ft. <u>150</u> Direction <u>West</u> Type <u>Ditch</u> Well disinfected upon completion? Yes ☒ No ☐
18. Elevation:		19. Remarks: Temporary Dewatering Well for Pumping Station (Storm Water) City of Wichita Southwest Industrial Sewer		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne Western Co. 102 Business name <u>Wichita, Kansas</u> License No. <u>12191</u> Address <u>12191</u> Signed <u>[Signature]</u> Date <u>12/19/79</u> Authorized representative		
						17. Pump: ☐ Not installed Manufacturer's name <u>LAYNE</u> Model number <u>12RR</u> HP <u>25</u> Volts <u>460</u> Length of drop pipe <u>40</u> ft. capacity <u>1000</u> g.p.m. Type: ☐ Submersible ☒ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5