

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>	Fraction $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	Section Number <u>26</u>	Township Number T <u>27</u> S	Range Number R <u>1</u> E/W <u>W</u>
--	---	-----------------------------	----------------------------------	---

Distance and direction from nearest town or city street address of well if located within city?

325 West, Wichita KS

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code	<u>Star Lumber</u> <u>325 S. West</u> <u>Wichita, KS 67231</u>	Board of Agriculture, Division of Water Resources Application Number:
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>59.50</u> ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered 1.50 ft. 2. 1.50 ft. 3. 1.50 ft.

WELL'S STATIC WATER LEVEL 1.50 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 1.50 ft. after 1.50 hours pumping 1.50 gpm

Est. Yield 1.50 gpm: Well water was 1.50 ft. after 1.50 hours pumping 1.50 gpm

Bore Hole Diameter 3.00 in. to TP ft., and TP in. to TP ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>Clamped</u>
------------------------------	----------------	-----------------	-------------------------------------

1 Steel 2 PVC

3 RMP (SR)

4 ABS

Blank casing diameter 2 in. to 49.50 ft. Dia 12/105H in. weight 12/105H lbs./ft. Wall thickness or gauge No. SC40

Casing height above land surface 12/105H in.

6 Asbestos-Cement

7 Fiberglass

9 Other (specify below)

Welded Threaded

TYPE OF SCREEN OR PERFORATION MATERIAL:	1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
	2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			

SCREEN-PERFORATED INTERVALS:	From <u>49.50</u> ft. to <u>59.50</u> ft.	From <u>49.50</u> ft. to <u>59.50</u> ft.	From <u>49.50</u> ft. to <u>59.50</u> ft.	From <u>49.50</u> ft. to <u>59.50</u> ft.
GRAVEL PACK INTERVALS:	From <u>16</u> ft. to <u>59.50</u> ft.	From <u>16</u> ft. to <u>59.50</u> ft.	From <u>16</u> ft. to <u>59.50</u> ft.	From <u>16</u> ft. to <u>59.50</u> ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
-------------------	---------------	----------------	-------------	---------

Grout Intervals: From 16 ft. to 16 ft., From 16 ft. to 16 ft., From 16 ft. to 16 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? NW How many feet? 600

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Br, silty, fine sand			
5	10	Brn, silty, fine to med sand			
10	24	Brn, fine to coarse sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3/11/92</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>324</u> This Water Well Record was completed on (mo/day/year) <u>3/13/92</u> under the business name of <u>Allied LAB</u> by (signature) <u>Richard J. Elg</u>
--