


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

SW NE NE NW

1. Location of well: <u>Sedgwick</u>		County: <u>1/4 NE 1/4 NW 4</u>		Section number: <u>28</u>		Township number: <u>T 27 S R 1 E</u>		Range number: <u>1 E</u>	
2. Distance and direction from nearest town or city: Street address of well location if in city: <u>337 Floyd Wichita, Kas.</u>				3. Owner of well: <u>L.A. Kosh</u> R.R. or street: <u>337 Floyd</u> City, state, zip code: <u>Wichita, Kansas</u>					
4. Locate with "X" in section below: N W E S 1 Mile Sketch map: 				6. Bore hole dia. <u>4</u> in. Completion date <u>9-2-76</u> Well depth <u>90</u> ft.					
5. Type and color of material				7. ☒ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary					
				8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☒ Lawn ☐ Oil field water ☐ Other					
				9. Casing: Material <u>thylene</u> Height <u>above</u> or below Threaded ☐ Welded ☒ Surface <u>12</u> in. RMP ☒ PVC ☐ Weight <u> </u> lbs./ft. Dia. <u>5</u> in. to <u>90</u> ft. depth Wall Thickness: inches or Dia. <u> </u> in. to <u> </u> ft. depth gage No. <u>200</u>					
				10. Screen: Manufacturer's name <u>Sunflower</u> Type <u>stippled</u> Dia. <u>5"</u> Slot gauze <u>106</u> Length <u>20'</u> Set between <u>70</u> ft. and <u>90</u> ft. Gravel pack? <u>yes</u> Size range of material <u>1/4"-1/8"</u>					
				11. Static water level: <u>25</u> ft. below land surface Date <u>9-2-76</u> mo./day/yr.					
(Use a second sheet if needed)				12. Pumping level below land surfaces: <u> </u> ft. after <u> </u> hrs. pumping <u> </u> g.p.m. <u> </u> ft. after <u> </u> hrs. pumping <u> </u> g.p.m. Estimated maximum yield <u> </u> g.p.m.					
				13. Water sample submitted: <u> </u> mo./day/yr. ☐ Yes ☐ No Date <u> </u>					
				14. Well head completion: ☒ Pitless adapter <u>12</u> inches above grade					
				15. Well grouted? <u>yes</u> With: ☐ Neat cement ☐ Bentonite ☒ Concrete Depth: From <u>40</u> ft. to <u>14</u> ft.					
				16. Nearest source of possible contamination <u>City</u> ft. <u>80</u> Direction <u>SW</u> Type <u>Surface</u> Well disinfected upon completion? ☒ Yes ☐ No					
18. Elevation: Topography: ☒ Hill ☒ Slope ☐ Upland ☐ Valley				17. Pump: Manufacturer's name <u>Hy-Rite</u> Model number <u>10682</u> HP <u>3/4</u> Volts <u>230</u> Length of drop pipe <u>53</u> ft. capacity <u>20</u> g.p.m. Type: ☒ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other					
				20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Thurswell & Pumps</u> License No. <u>236</u> Business name <u>Wichita, Kas.</u> Address <u> </u> Signed <u>M. Arnold</u> Date <u>3-10-77</u> Authorized representative					
				19. Remarks:					
				21. Remarks:					
				22. Remarks:					

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5