


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

SW NE NW NW

1. Location of well: <u>Sedgwick</u>		County	Fraction	Section number	Township number	Range number
			<u>1/4 NW 1/4 NW</u>	<u>28</u>	T <u>27S</u> S R <u>1</u> E <u>W</u>	
2. Distance and direction from nearest town or city: <u>341 Turquoise</u>		3. Owner of well: <u>H. J. Hawery</u>		R.R. or street: <u>1621 South Gordon</u>		
Street address of well location if in city: <u>Wichita, Ks.</u>		City, state, zip code: <u>Wichita Kansas</u>				
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. <u>11</u> in. Completion date <u>7-26-76</u>		
				Well depth <u>125</u> ft.		
5. Type and color of material		From	To	7. Cable tool ☒ Rotary ☐ Driven ☐ Dug		
<u>Topsoil</u>		<u>0</u>	<u>3</u>	☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary		
<u>Brown clay</u>		<u>3</u>	<u>23</u>	8. Use: ☒ Domestic ☐ Public supply ☐ Industry		
<u>Fine sand</u>		<u>23</u>	<u>85</u>	☐ Irrigation ☐ Air conditioning ☐ Stock		
<u>Gray clay</u>		<u>85</u>	<u>98</u>	☐ Lawn ☐ Oil field water ☐ Other		
<u>Medium sand</u>		<u>98</u>	<u>125</u>	9. Casing: Material <u>stylene</u> Height: <u>12</u> ft. or below		
				Threaded ☐ Welded ☐ Surface ☐ Dia. <u>5 1/2</u> in.		
				RMP ☒ PVC ☐ Weight <u>125</u> lbs./ft.		
				Dia. <u>5</u> in. <u>125</u> ft. depth Wall Thickness: inches or		
				Dia. <u>5</u> in. to <u>125</u> ft. depth gage No. <u>200</u>		
				10. Screen: Manufacturer's name <u>Sunflower Plastics</u>		
				Type <u>stylene</u> Dia. <u>5 1/2</u> in.		
				Slot gauze <u>20</u> mesh Length <u>30</u> ft.		
				Set between <u>10.5</u> ft. and <u>12.5</u> ft.		
				<u>yes</u> ft. and <u>14-18</u> ft.		
				Gravel pack? <u>yes</u> size range of material <u>1/4-1/8"</u>		
				11. Static water level: <u>30</u> ft. below land surface Date <u>7-26-76</u>		
				mo./day/yr. <u>7-26-76</u>		
				12. Pumping level below land surfaces:		
				<u>30</u> ft. after <u>1</u> hrs. pumping <u>230</u> g.p.m.		
				<u>30</u> ft. after <u>1</u> hrs. pumping <u>230</u> g.p.m.		
				Estimated maximum yield <u>230</u> g.p.m.		
				13. Water sample submitted: <u>30</u> mo./day/yr.		
				☐ Yes ☐ No Date <u>7-26-76</u>		
				14. Well head completion: <u>12</u> inches above grade		
				☒ Pitless adapter <u>12</u> inches above grade		
				15. Well grouted <u>yes</u>		
				With: <u>40</u> Neapement <u>14</u> Bentonite ☒ Concrete		
				Depth: From <u>40</u> ft. to <u>14</u> ft.		
				16. Nearest source of possible contamination: <u>City</u>		
				ft. <u>15</u> Direction <u>West</u> Type <u>Subs</u>		
				Well disinfected upon completion? ☒ Yes ☐ No		
				17. Pump: <u>Not installed</u>		
				Manufacturer's name <u>Sta-Rite</u>		
				Model number <u>LP602</u> HP <u>3/4</u> Volt <u>230</u>		
				Length of drop pipe <u>30</u> ft. capacity <u>20</u> g.p.m.		
				Type ☒ Submersible ☐ Turbine		
				☐ Jet ☐ Reciprocating		
				☐ Centrifugal ☐ Other		
18. Elevation:	19. Remarks: <u>Flat Ground</u>		20. Water well contractor's certification:			
Topography:			This well was drilled under my jurisdiction and this report			
☐ Hill			is true to the best of my knowledge and belief.			
☐ Slope			<u>Harp Well Pump</u> <u>236</u>			
☐ Upland			Business name <u>Wichita Kansas</u> License No. <u>236</u>			
☐ Valley			Address <u>Wichita Kansas</u>			
			Signed <u>M. Orsall</u> Date <u>8-25-76</u>			
			Authorized representative <u>8-25-76</u>			

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5