


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction NE 1/4 NE 1/4 NW 1/4	Section Number 28	Township Number T 27 S	Range Number R 1 W 1/2
Distance and direction from nearest town or city street address of well if located within city? 436 Floyd Wichita, Kansas					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Margaret Clark 436 Floyd Wichita, Kansas			
		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 67 ft. ELEVATION: Depth(s) Groundwater Encountered 17 ft. 2. ft. 3. ft. 4-29-86 WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 <u>Domestic</u> 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes XX No XX If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XX No			
5 TYPE OF BLANK CASING USED: 1 Steel <u>3 RMP (SR)</u> 2 PVC 4 ABS Blank casing diameter 5 in. to 47 ft. Dia 67 in. to ft. Dia in. to ft. Casing height above land surface 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No. .203		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass <u>Cer-Mac styrene SDR-26</u> Threaded			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass <u>8 RMP (SR)</u> 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)		SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 <u>Drilled holes</u> 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 47 ft. to 67 ft. From ft. to ft. From ft. to ft. From ft. to ft.		GRAVEL PACK INTERVALS: From 14 ft. to 67 ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement <u>2 Cement grout</u> 3 Bentonite 4 Other Grout Intervals: From 4 ft. to 14 ft. From ft. to ft. From ft. to ft.		What is the nearest source of possible contamination: 1 <u>Septic tank</u> 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 <u>Sewer lines</u> 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? East How many feet? 81			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0	3	Topsoil			
3	18	Clay			
18	39	Fine Sand			
39	43	clay			
43	67	Medium Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-29-86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 5-20-86 under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Mary Arnold</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					