


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NW 1/4 NW 1/4 SW 1/4	28	T 27 S	R 1 E/W
Distance and direction from nearest town or city street address of well if located within city? Located at address 8730 West Kellogg, Wichita, Kansas					
HWST Job No.: 74-40/4017.01					
2 WATER WELL OWNER:		SECURITY OIL COMPANY			
RR#, St. Address, Box # :		8730 W. Kellogg			
City, State, ZIP Code :		Wichita, Kansas 67209			
Board of Agriculture, Division of Water Resources		Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 40.0 ft. ELEVATION: TOC 1330.51'			
		Depth(s) Groundwater Encountered 1. 31.0 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 32.20 ft. below land surface measured on mo/day/yr 6/4/90			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 6 in. to 40.0 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well MW-1			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded			
2 PVC 4 ABS		7 Fiberglass Threaded X			
Blank casing diameter 2.0 in. to 15.0 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface flush in. weight lbs./ft. Wall thickness or gauge No. Sch 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		X PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot X Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 40.0 ft. to 15.0 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 40.0 ft. to 22.8 ft. From ft. to ft.					
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout X Bentonite 4 Other			
Grout Intervals: From 20.4 ft. to grade ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 1X Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? North		How many feet? 50.0			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	0.2	ASPHALT:			
0.2	12.5	CLAY: brown.			
12.5	17.0	SANDY CLAY: reddish-brown; fine to medium grained sand.			
17.0	21.0	SAND: fine to coarse sand; 5-10% gravel.			
21.0	27.0	SAND: brown-red; medium to coarse; 15-20% gravel.			
27.0	32.0	SAND: pale brown; fine to coarse sand.			
32.0	34.0	COARSE GRAVEL:			
34.0	40.0	CLAY/SAND MIXTURE:			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (X) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/29/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 471 This Water Well Record was completed on (mo/day/yr) 7/26/90 under the business name of HWS Technologies Inc. by (signature) Richard A. Smith					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					