

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>	$\frac{1}{4}$ <u>NC</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$	<u>28</u>	T <u>27</u> S	R <u>1W</u> <u>E/W</u>

Distance and direction from nearest town or city street address of well if located within city?

8220 West Harry Wichita, Ks. Refer to horizontal location of MW-1 through MW-7 map

2 WATER WELL OWNER: <u>Learjet</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>8220 W. Harry</u>	Application Number:
City, State, ZIP Code: <u>Wichita, Ks.</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>52.88</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>31.60</u> ft. below land surface measured on mo/day/yr <u>9-5-90</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: <u>7 3/4</u> in. to ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC sch 40	7 Fiberglass		Threaded. <u>flush joint</u>
4 ABS			
Blank casing diameter <u>2</u> in. to <u>25</u> ft. Dia			
Casing height above land surface: <u>see schedule</u> in, weight <u>.703</u> lbs./ft. Wall thickness or gauge No. <u>.154</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC Sch 40	10 Asbestos-cement	
1 Steel	8 RMP (SR)	11 Other (specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless steel			
4 Galvanized steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
4 Key punched			
SCREEN-PERFORATED INTERVALS: From <u>25.38</u> ft. to <u>52.88</u> ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From <u>22.85</u> ft. to <u>52.88</u> ft. From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other <u>see schedule</u>
Grout Intervals: From <u>0</u> ft. to <u>2</u> ft. From <u>2</u> ft. to <u>22.85</u> ft. From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage	<u>unknown</u>		
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				
Direction from well?	How many feet?			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	topsoil			
2	14	brown clay			
14	19	very fine to fine sand			
19	29	fine to coarse sand			
		fine to medium gravel			
29	53	fine to coarse sand			
		fine to coarse gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-5-90</u> and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. <u>236</u> This Water Well Record was completed on (mo/day/yr) <u>9-28-90</u>
under the business name of <u>Harp Well and Pump Service, Inc.</u> by (signature) <u>Mary Arnold</u>