

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		$\frac{1}{4}$ <u>NC</u> $\frac{1}{4}$ SW $\frac{1}{4}$	<u>28</u>	T <u>27</u> S	R <u>1W</u> E <u>(NW)</u>
Distance and direction from nearest town or city street address of well if located within city? <u>8220 West Harry Wichita, Ks. Refer to horizontal location of MW-1 through MW-7 map</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # : <u>8220 West Harry</u>		Application Number:			
City, State, ZIP Code : <u>Wichita, Ks.</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>54.5</u> ft. ELEVATION:			
1 Mile		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>36.68</u> ft. below land surface measured on mo/day/yr <u>8-10-90</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter <u>7 3/4</u> in. to ft., and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic		3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation		4 Industrial	7 Lawn and garden only	10 <u>Monitoring well</u>	
Was a chemical/bacteriological sample submitted to Department? Yes.....No <u>X</u>; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No <u>X</u>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC <u>schedule 40s</u>		7 Fiberglass			Threaded <u>flush joint</u>
Blank casing diameter <u>2</u> in. to <u>22.5</u> ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface <u>see schedule</u> in., weight <u>.703</u> lbs./ft. Wall thickness or gauge No. <u>154</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC <u>sch 40</u>			
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut			
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes	11 None (open hole)
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From <u>22.5</u> ft. to <u>54.5</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>30.1</u> ft. to <u>54.5</u> ft., From ft. to ft.					
6 GROUT MATERIAL:		hole plug <u>see schedule</u>			
1 Neat cement		2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From <u>0</u> ft. to <u>5</u> ft., From <u>5</u> ft. to <u>30</u> ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens			
1 Septic tank		4 Lateral lines	7 Pit privy	11 Fuel storage	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)
Direction from well?		How many feet? <u>unknown</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	topsoil			
2	15	brown clay			
15	20	sandy brown clay			
20	35	fine to coarse sand			
		fine to medium gravel			
35	55	fine to coarse sand			
		fine to coarse gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-10-90</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>236</u> This Water Well Record was completed on (mo/day/yr) under the business name of <u>Harp Well and Pump Service, Inc.</u> by (signature)					