


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction SW 1/4 SE 1/4 SE 1/4		Section Number 28	Township Number T 27 S	Range Number R 1W E/W
Distance and direction from nearest town or city street address of well if located within city? 8220 West Harry Wichita, KS.						
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		LEAR Jet 8220 West Harry Wichita, KS. Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 66 ft. ELEVATION: 3-26-91 ft. Depth(s) Groundwater Encountered 1. 27.98 ft. 2. 27.98 ft. 3. 27.98 ft. WELL'S STATIC WATER LEVEL 27.98 ft. below land surface measured on mo/day/yr Pump test data: Well water was 27.98 ft. after 27.98 hours pumping 27.98 gpm Est. Yield 27.98 gpm: Well water was 27.98 ft. after 27.98 hours pumping 27.98 gpm Bore Hole Diameter 6 in. to 6 in. and 6 in. to 6 in. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes X No XX If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No XX				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC sch 40 4 ABS Blank casing diameter 2 in. to 46 ft., Dia 46 in. to 46 ft., Dia 46 in. to 46 ft. Casing height above land surface see schedule weight 703 lbs./ft. Wall thickness or gauge No. 154		CASING JOINTS: Glued flush joint Clamped flush joint Welded flush joint Threaded flush joint TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 10 slot 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 10 slot 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) 10 slot SCREEN-PERFORATED INTERVALS: From 46 ft. to 66 ft., From 46 ft. to 66 ft., From 46 ft. to 66 ft. GRAVEL PACK INTERVALS: From 42 ft. to 66 ft., From 42 ft. to 66 ft., From 42 ft. to 66 ft.				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite see sch 4 Other see sch Grout Intervals: From 0 ft. to 42 ft., From 42 ft. to 66 ft., From 66 ft. to 66 ft., From 66 ft. to 66 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) unknown 13 Insecticide storage Direction from well? How many feet?						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-26-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 4-20-91 under the business name of Harp Well & Pump Service, Inc. by (signature) Mary Arnold						

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.