

1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction NW 1/4 NW 1/4 SW 1/4		Section Number 28	Township Number 27 S	Range Number 1 W EW
Distance and direction from nearest town or city street address of well if located within city? NE Corner of Tyler Road and West Hiway 54 Wichita, KS. Security Oil Company #2						
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Phillips 66 1254 South Tyler Road Wichita, KS. 67209 Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 1 Mile N W E S NW NE SW SE		4 DEPTH OF COMPLETED WELL..... 40 ft. ELEVATION: Depth(s) Groundwater Encountered 1..... ft. 2..... ft. 3..... ft. WELL'S STATIC WATER LEVEL .. 32.30 .. ft. below land surface measured on mo/day/yr 2-21-92 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter..... 8 in. to 40 ft., and..... in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No..... XX ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No XX				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC sch 40 4 ABS Blank casing diameter 2 in. to 25 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface. Flush Mount in., weight 703 lbs./ft. Wall thickness or gauge No. 154 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 25 ft. to 40 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 22.8 ft. to 40 ft. From ft. to ft. From ft. to ft. From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 1 ft. From ft. to 22.8 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage NA Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 3 Topsoil 3 15 clay 15 35 Fine silty sand 35 40 Medium to co/arise sand						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-21-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/year) 2-20-92 under the business name of Harp Well & Pump Service, Inc. by (signature) Mary Arnold						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						

PHONE
(316) 722-1411



HARP WELL & PUMP SERVICE, INC.

Water Well Drilling - Piling Hole Drilling - Test Drilling
Gravel Packed Wells for
Home - Industrial - Municipal - Irrigation
PUMP SALES & SERVICE

215 SO. TYLER ROAD

WICHITA, KANSAS 67209

Date 2-21-92

Schrader Bros. Constr. Co.
JOB/ Security Oil Company, Tyler Road & Kellogg
MW-1

Depth - Log
0

Description

	Height of Protective Housing above Ground Surface: <u>Flush mounted</u>
	Elevation of Top of Primary Casing: _____
	Length of Protective Housing: _____
	Type of Protective Cap: <u>Flush mounted</u>
	Ground Surface Elevation: _____
	Depth to Bottom of Surface Casing if Used: <u>NA</u>
	Type of Surface Seal: <u>Cement</u>
	Inside Diameter of Primary Casing: <u>2"</u>
	Primary Casing Material: <u>PVC</u> <u>Schedule 40</u>
	Diameter of Borehole: <u>6"</u>
	Type of Backfill: <u>Bentonite hole plug</u>
	Depth to Top of Seal: <u>20.4'</u>
	Type of Seal: <u>Bentonite</u>
	Depth to Top of Gravel Pack: <u>22.8'</u>
	Type of Packing: <u>Silica Sand #8 and natural Sand</u>

	Depth to Top of Screen: <u>25'</u>
	I.D. of Well Screen: <u>2"</u>
	Type of Well Screen: <u>PVC 10 slot</u> <u>Schedule</u>
	Depth to Bottom of Screen: <u>40'</u>
	Type of Bottom Cap: <u>Pointed end</u> <u>Cap PVC</u>
	Depth to Bottom of Borehole: <u>40'</u>

RECEIVED

MAY 1 8 1992

DIVISION OF
ENVIRONMENT