


1 LOCATION OF WATER WELL: SEDGWICK County		Fraction NW 1/4 SE 1/4 SE 1/4	Section Number 29	Township Number T 27 S	Range Number R 1 W
Distance and direction from nearest town or city street address of well if located within city? F. J. Decker 527 South Byron Wichita, Kansas					
2 WATER WELL OWNER: F. J. Decker RR#, St. Address, Box # : 527 South Byron City, State, ZIP Code : Wichita, Kansas Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 25 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr 5-31-85			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter 1.1 in. to ft. and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic 3 Feedlot 6 Oil field water supply		5 Public water supply 8 Air conditioning 11 Injection well			
2 Irrigation 4 Industrial 7 Lawn and garden only		9 Dewatering 12 Other (Specify below)			
10 Observation well		Was a chemical/bacteriological sample submitted to Department? Yes.....No..... XX If yes, mo/day/yr sample was submitted			
Water Well Disinfected? Yes XX No		5 TYPE OF BLANK CASING USED:			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)		CASING JOINTS: Glued XX Clamped			
2 PVC 4 ABS 7 Fiberglass Cer-Mac styrene SDR-26		Welded			
Blank casing diameter 5 in. to 20 ft. Dia. in. to ft. Dia. in. to ft.		Threaded			
Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203		TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		7 PVC 10 Asbestos-cement			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut		11 None (open hole)			
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
7 Torch cut 10 Other (specify)		SCREEN-PERFORATED INTERVALS: From 20 ft. to 60 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 14 ft. to 60 ft., From ft. to ft.		From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 4 ft. to 14 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? West How many feet? 51					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Topsoil			
3	15	Clay			
15	27	Fine Sand			
27	40	Medium Sand			
40	42	Clay			
42	60	Fine Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-31-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 6-16-85 under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Mary Arnold</i>					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					