

1 LOCATION OF WATER WELL:		Fraction		Township Number		Range Number	
County: SEDGWICK		SW 1/4 NW 1/4 NW 1/4		29 T 27 S		R 1 W E/W	
Distance and direction from nearest town or city street address of well if located within city?							
638 Wetmore Drive, Wichita, Ks.							
2 WATER WELL OWNER:		Jerry Blue		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		638 Wetmore Drive		Application Number:			
City, State, ZIP Code :		Wichita, Ks.					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION:					
		Depth(s) Groundwater Encountered 1. 15 ft. 2. ft. 3. ft.					
		WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 4-26-82					
		Pump test data: Well water was ft. after hours pumping gpm					
		Est. Yield gpm: Well water was ft. after hours pumping gpm					
Bore Hole Diameter 11 in. to ft., and in. to ft.		WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted					
5 TYPE OF BLANK CASING USED:		Casing Joints: Glued X Clamped					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile					
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)					
Blank casing diameter 5 in. to 20 ft. Dia in. to ft. Dia		Cer-Mac Styrene SDR-26 in. to ft. Dia					
Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203		TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify)					
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)		2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
SCREEN-PERFORATED INTERVALS: From 20 ft. to 50 ft. From ft. to ft. From ft. to ft.		GRAVEL PACK INTERVALS: From 14 ft. to 50 ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 4 ft. to 14 ft. From ft. to ft. From ft. to ft.		What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)		13 Insecticide storage					
Direction from well? North		How many feet? 97					
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG					
0 10 Dirt							
10 15 Fine Sand							
15 40 Sand and Gravel							
40 60 Blue Clay							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-26-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 6-17-82 under the business name of Harp Well & Pump Serv., Inc. by (signature) M. Arnold							
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							