


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

SW SW NE NE

1. Location of well:	County Sedgwick	Fraction 1/4 NE 1/4 NE 1/4	Section number 29	Township number T 27 S	Range number R 1 W
2. Distance and direction from nearest town or city: Street address of well location if in city:			3. Owner of well: R.R. or street: City, state, zip code:		
459 Maybelle Wichita, Kansas			Richard Price 1537 North Battin Wichita, Kansas		
4. Locate with "X" in section below: Sketch map: 			6. Bore hole dia. 11 in. Completion date Well depth 113 ft. 2-12-77		
5. Type and color of material			7. ☒ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary		
Topsoil			8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other		
Sandy Clay			9. Casing: Material styrene Height: Above or below Threaded ☐ Welded ☐ Surface 12 in. RMP ☒ PVC ☐ Weight ☐ lbs./ft. Dia. 5 in. to 113 ft. depth Wall Thickness: inches or Dia. ☐ in. to ☐ ft. depth gage No. 200		
Sandy Soil			10. Screen: Manufacturer's name Sunflower Plastic Type styrene Dia. 5" Slot 1/16 .06 Length 13' Set between 100 ft. and 113 ft. ft. and ☐ ft. Gravel pack? ☒ yes size range of material 1/4-1/8"		
Fine Sand			11. Static water level: 29 ft. below land surface Date 2-12-77		
Coarse Sand			12. Pumping level below land surfaces: ft. after ☐ hrs. pumping ☐ g.p.m. ft. after ☐ hrs. pumping ☐ g.p.m. Estimated maximum yield ☐ g.p.m.		
Coarse sand with gravel			13. Water sample submitted: ☐ Yes ☐ No Date ☐		
			14. Well head completion: ☒ Pitless adapter 12 inches above grade		
			15. Well grouted? ☒ yes With: ☐ Neat cement ☐ Bentonite ☒ Concrete Depth: From 40' ft. to 14 ft.		
			16. Nearest source of possible contamination: Septic Tank ft. 90 Direction West Type Tank Well disinfected upon completion? ☒ Yes ☐ No		
			17. Pump: ☐ Not installed Manufacturer's name Sta-Rite Model number 20P4D02 HP 3/4 Volts 230 Length of drop pipe 50 ft. capacity 20 g.p.m. Type: ☒ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other		
18. Elevation:			20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Harp Well & Pump 236 Business name Wichita, Kansas License No. Address Wichita, Kansas Signed M. Arnold Date 3-10-77 Authorized representative		
19. Remarks: Flat Ground					
Topography: ☐ Hill ☐ Slope ☐ Upland ☐ Valley					

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5