

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Sedgwick	Fraction 1/4 NE 1/4 NW 1/4	Section number 30	Township number T 27 S	Range number R 1W E/W															
2. Distance and direction from nearest town or city: Street address of well location if in city:			3. Owner of well: H.W. Keys Construction R.R. or street: P.O.Box 9271 City, state, zip code: Wichita, Kansas																		
4. Locate with "X" in section below: N 1 Mile W E S 1 Mile			<table border="1" style="width: 100px; height: 100px; text-align: center; border-collapse: collapse;"> <tr><td> </td><td>X</td><td> </td></tr> <tr><td>NW</td><td> </td><td>NE</td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td>SW</td><td> </td><td>SE</td></tr> <tr><td> </td><td> </td><td> </td></tr> </table> Sketch map:					X		NW		NE				SW		SE			
	X																				
NW		NE																			
SW		SE																			
5. Type and color of material			From	To	6. Bore hole dia. 11 in. Completion date 7-18-77 Well depth 145 ft. 7. ☐ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary 8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other 9. Casing: Material Styrene Height: Above or below Threaded ☐ Welded g1 Surface 12 in. RMP ☒ PVC ☐ Weight ☐ lbs./ft. Dia. 5 in. to 145 ft. depth Wall Thickness: inches or Dia. ☐ in. to ☐ ft. depth gage No. .200																
Topsoil			0	3	10. Screen: Manufacturer's name Sunflower Plastic Type Styrene Dia. 5" Slot/gauge .06 Length 15' Set between 130 ft. and 145 ft. ft. and ☐ ft. Gravel pack? yes Size range of material 1/2-1/8"																
Clay			3	30	11. Static water level: ☐ mo./day/yr. 32 ft. below land surface Date 7-18-77																
Fine Sand			30	38	12. Pumping level below land surfaces: ☐ ft. after ☐ hrs. pumping ☐ g.p.m. ☐ ft. after ☐ hrs. pumping ☐ g.p.m. Estimated maximum yield ☐ g.p.m.																
Medium Sand			38	59	13. Water sample submitted: ☐ mo./day/yr. ☐ Yes ☐ No Date ☐																
Clay			59	76	14. Well head completion: Well Seal ☐ Pitless adapter 12 inches above grade																
Fine Sand			76	120	15. Well grouted? yes to 2 fine sand mix. With: ☐ Neat cement ☐ Bentonite ☒ Concrete Depth: From 6 ft. to 16 ft.																
Clay			120	128	16. Nearest source of possible contamination: NONE ft. ☐ Direction ☐ Type ☐ Well disinfected upon completion? ☒ Yes ☐ No																
Medium Sand			128	145	17. Pump: ☐ Not installed Manufacturer's name Sta-Rite Model number 20P4D02 HP 3/4 Volts 230 Length of drop pipe 50 ft. capacity 20 g.p.m. Type: ☒ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other																
(Use a second sheet if needed)					20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Harp Well & Pump 236 Business name License No. Address Wichita, Kansas Signed M. Arnold Date 7-19-77 Authorized representative																
18. Elevation:		19. Remarks:																			
Topography: ☐ Hill ☒ Slope ☐ Upland ☐ Valley		Septic System was not installed when the well was drilled. No Apparent source for contamination. Well is to be in the basement.																			

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5