

CORRECTION TO WATER WELL RECORD (WWC-5)

The following correction(s) was made to the attached WWC-5 log, in order to file the item or to rectify lacking or incorrect information.

Fraction (1/4 1/4 1/4) Section-Township-Range changed:

listed as 30-27S-1W

changed to NE SE SE, 30-27S-1W

Other changes: Initial statements: _____

Changed to: _____

Comments: _____

verification method: Well address, legal description, city map,

and Wichita West 1:24,000 topo. map. initials: DRL date: 10/24/2001


submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment Bureau of Water Industrial Programs, Bldg 283, Forbes Field, KS 66620

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County Sedgwick	Township name Delano	Fraction	Section number 30	Town number 27S	Range number 1W	
Distance and direction from nearest town or city: 1350 Leecrest			3 Owner of well: Gerald Hadsall				
Street address of well location if in city: Wichita, Kansas			Address: 1350 Leecrest Wichita, Kansas 67209				
Locate with "X" in section below: 			Sketch map:			4 Well depth: 143 ft. Date of completion 4-23-75 Well diameter 11 in.	
2 Type and color of material			From		To		5 ☐ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary
							6 Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Commercial ☐ Test well ☐
Dirt and Top Soil			0		2		7 Casing: Material Styrene Height: above/below 44 Threaded ☐ Welded ☐ Surface 12 in. Digm. 5 in. to 143 ft. depth Drive shoe? ☐ Yes ☐ No — in. to — ft. depth
Clay			2		24		8 Screen: Manufacturer Sunflower Plastic Type Styrene Dio. 5" Slot/gauze 005 Length 20' Set between 123 ft. and 143 ft. Fittings: Gravel pack ☒ Yes ☐ No Size range of material 1-1/8"
Sandy Clay			24		52		9 Static water level: 25 ft. below land surface Date 4-23-75
Medium fine Sand			52		75		10 Pumping level below land surfaces: — ft. after — hrs. pumping — g.p.m. — ft. after — hrs. pumping — g.p.m. Estimated maximum yield — g.p.m.
Clay			75		90		11 Water sample submitted: ☐ Yes ☐ No Date —
Fine Sand			90		105		12 Well head completion: ☒ Pitless adapter 12 ☒ Inches above grade
Clay			105		125		13 Well grouted? ☒ Yes ☐ No ☒ Neat cement ☐ Bentonite ☐ Depth: From 0 ft. to 12 ft.
Medium Fine Sand			125		143		14 Nearest source of possible contamination: ft. 100 Direction East Type Septic Well disinfected upon completion? ☒ Yes ☐ No
(use a second sheet if needed)							15 Pump: ☐ Not installed Manufacturer's name Sta-Rite Model number IP602 HP 3/4 Volts 230 Length of drop pipe 55 ft. capacity 20 g.m.p. Type: ☒ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other
16 Remarks: elevation							17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Harp Well & Pump Serv. 236 Business name Wichita, Kansas License No. 67209 Address 27. Arnold Date 4-24-75 Signed 27. Arnold Authorized representative

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5