

1 LOCATION OF WATER WELL:		WATER WELL RECORD		TOWNSHIP NUMBER		RANGE NUMBER	
County: Sedgwick		Fraction SE 1/4 SE 1/4 SE 1/4		Section Number 31		Township Number T 27 S	
Distance and direction from nearest town or city street address of well if located within city?						Range Number R 1 W E/W	
10304 W. Pawnee		Wichita, Ks.					
2 WATER WELL OWNER: Builder Development						Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box # : 1530 So. Oliver						Application Number:	
City, State, ZIP Code : Wichita, Ks.							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 125 ft. ELEVATION:					
		Depth(s) Groundwater Encountered 1. 35 ft. 2. 35 ft. 3. 35 ft.					
		WELL'S STATIC WATER LEVEL 35 ft. below land surface measured on mo/day/yr 5-23-85					
		Pump test data: Well water was 35 ft. after 5 hours pumping 35 gpm					
		Est. Yield 35 gpm: Well water was 35 ft. after 5 hours pumping 35 gpm					
		Bore Hole Diameter 11 in. to 11 ft., and 11 in. to 11 ft.					
WELL WATER TO BE USED AS:		5 Public water supply		8 Air conditioning		11 Injection well	
1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering	
2 Irrigation		4 Industrial		7 Lawn and garden only		10 Observation well	
Was a chemical/bacteriological sample submitted to Department? Yes X No X		If yes, mo/day/yr sample was submitted				Water Well Disinfected? Yes X No X	
5 TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued X Clamped X	
1 Steel		3 RMP (SR)		6 Asbestos-Cement		9 Other (specify below)	
2 PVC		4 ABS		7 Fiberglass		Cer-Mac styrene SDR-26	
Blank casing diameter 5 in. to 95 ft., Dia 5 in. to 95 ft., Dia 5 in. to 95 ft.							
Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC		10 Asbestos-cement			
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)	
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut		11 None (open hole)	
1 Continuous slot		3 Mill slot		6 Wire wrapped		9 Drilled holes	
2 Louvered shutter		4 Key punched		7 Torch cut		10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		From 95 ft. to 125 ft.		From 95 ft. to 125 ft.		From 95 ft. to 125 ft.	
GRAVEL PACK INTERVALS:		From 14 ft. to 125 ft.		From 14 ft. to 125 ft.		From 14 ft. to 125 ft.	
6 GROUT MATERIAL:		1 Neat cement		2 Cement grout		3 Bentonite	
Grout Intervals: From 4 ft. to 14 ft.						4 Other	
What is the nearest source of possible contamination:		10 Livestock pens		14 Abandoned water well			
1 Septic tank		4 Lateral lines		7 Pit privy		11 Fuel storage	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		12 Fertilizer storage	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		13 Insecticide storage	
Direction from well?						How many feet?	
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG		
0	3	Topsoil					
3	17	Clay					
17	35	Fine Sand					
35	95	Clay					
95	125	Medium Sand					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-23-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 6-16-85 under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Mary Arnold</i>							
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							