

1 LOCATION OF WATER WELL: County: SEDERWICK Fraction: NE 1/4 SE 1/4 NE 1/4 Section Number: 34 Township Number: T 27 S Range Number: R 1 EW

Distance and direction from nearest town or city street address of well if located within city?
1809 So Hoover WICHITA KANS

2 WATER WELL OWNER: SUELLEN TRAU B CONSTRUCTION
RR#, St. Address, Box #: 632 SEVILLE, WICHITA KS Board of Agriculture, Division of Water Resources
City, State, ZIP Code: 67209 Application Number: NONE

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	NW	NE	
		X	
	SW	SE	E
			S

4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: 1300
Depth(s) Groundwater Encountered: 9.5 ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL: 9.5 ft. below land surface measured on mo/day/yr 2-23-82
Pump test data: Well water was NA ft. after NA hours pumping NA gpm
Est. Yield 80 gpm: Well water was NA ft. after NA hours pumping NA gpm
Bore Hole Diameter: 9 in. to 9.5 ft., and 6 in. to 35 ft.
WELL WATER TO BE USED AS:
☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
☐ 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☐
 Water Well Disinfected? Yes ☒ No ☐

5 TYPE OF BLANK CASING USED:
 1 Steel ☒ 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: ☒ Glued ☐ Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ☐
 Blank casing diameter: 5 in. to 28 ft., Dia. 1.59 in. to 209 ft.
 Casing height above land surface: 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 209
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass ☒ 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) ☐
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 7 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ☐
 SCREEN-PERFORATED INTERVALS: From 27 ft. to 35 ft., From ☐ ft. to ☐ ft.
 From ☐ ft. to ☐ ft., From ☐ ft. to ☐ ft.
 GRAVEL PACK INTERVALS: From ☐ ft. to ☐ ft., From ☐ ft. to ☐ ft.
 From ☐ ft. to ☐ ft., From ☐ ft. to ☐ ft.
 6 GROUT MATERIAL: ☒ Neat cement ☒ Cement grout 3 Bentonite 4 Other ☐
 Grout Intervals: From 0 ft. to 9.5 ft., From ☐ ft. to ☐ ft., From ☐ ft. to ☐ ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
☒ Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NORTH How many feet? 12

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2.5	RED CLAY			
2.5	6	SAND BROWN FINE			
6	10	SAND TAN MED			
10	20	SAND TAN COARSE			
20	22	CLAY LIGHT GRAY			
22	26	SAND TAN FINE			
26	35	SAND TAN COARSE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-23-82 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 104 This Water Well Record was completed on (mo/day/yr) 2-23-82
 under the business name of BEARDEN Pump & Well by (signature) Ch. W. Beard
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

27

R

EW

SEC.

34

NE 1/4

SE 1/4

NE 1/4

JUL 21 1982