

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SE 1/4 NE 1/4 NE 1/4	35	T 27 S	R 1 E
Distance and direction from nearest town or city street address of well if located within city? 1835 SO. WEST ST. WICHITA KANS					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #		Application Number:			
City, State, ZIP Code		1855 SO. WEST ST. 67209 WICHITA KANS			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL			
		36 ft. ELEVATION: 1300			
		Depth(s) Groundwater Encountered 1. 14 ft. 2. 14 ft. 3. 14 ft.			
		WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr 5/18/83			
		Pump test data: Well water was NA ft. after NA hours pumping NA gpm			
		Est. Yield 60 gpm Well water was NA ft. after NA hours pumping NA gpm			
		Bore Hole Diameter 10 in. to 13 ft. and 6 in. to 36 ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☐ If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		Water Well Disinfected? ☒ Yes ☐ No			
1 Steel 3 AMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: ☒ Glued ☐ Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
Blank casing diameter 5 in. to 1228 ft. Dia 1.55 in. to 209 ft.					
Casing height above land surface 1228 in. weight 1.55 lbs./ft. Wall thickness or gauge No. 209					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 AMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS:		From 27 ft. to 36 ft. From 36 ft. to 36 ft.			
GRAVEL PACK INTERVALS:		From 36 ft. to 36 ft. From 36 ft. to 36 ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 3 ft. to 13 ft. From 13 ft. to 13 ft. From 13 ft. to 13 ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? SE		How many feet? 75			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0	3	BLACK TOP SOIL			
3	9	SANDY BROWN SOIL			
9	18	SAND TAN MED			
18	24	SAND TAN COARSE			
24	32	SAND TAN MED			
32	36	SAND LT. GREY COARSE			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/18/83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 104 This Water Well Record was completed on (mo/day/yr) 5/21/83 under the business name of BEARDEN PUMP & WELL by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

27

R

E

SEC.

35

SE 1/4

NE 1/4

NE 1/4

NE 1/4