


MW-3

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SE 1/4 NW 1/4 NE 1/4	35	T 27 S	R 1 E/W
Distance and direction from nearest town or city street address of well if located within city?					
1660 Baehr, Wichita KS					
2 WATER WELL OWNER:		Johnson Control, Inc			
RR#, St. Address, Box #		4285 N. Port Washington Rd.			
City, State, ZIP Code		Milwaukee, WI 53212			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 30.0 ft. ELEVATION: NA			
		Depth(s) Groundwater Encountered 1. 12.60 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 13.18 ft. below land surface measured on mo/day/yr 10-7-92			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded Flush			
5 Wrought iron 8 Concrete tile					
6 Asbestos-Cement 9 Other (specify below)					
7 Fiberglass					
Blank casing diameter in. to ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface Flush in., weight 170.3 lbs./ft. Wall thickness or gauge No. 154					
TYPE OF SCREEN OR PERFORATION MATERIAL:		PVC			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		10 Asbestos-cement			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot 3 Mill slot		8 Saw cut 11 None (open hole)			
2 Louvered shutter 4 Key punched		9 Drilled holes			
SCREEN-PERFORATED INTERVALS: From 9.55 ft. to 29.55 ft., From ft. to ft.		10 Other (specify)			
GRAVEL PACK INTERVALS: From 8.55 ft. to 29.55 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 8.55 ft. to 1.0 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	0.5	Asphalt			
0.5	5.0	Silt, brown, very sandy			
5.0	7.0	Sand, very fine, well sorted			
		very silty			
7.0	20.0	Sand, fine to medium			
		grained, well sorted, Angular			
20.0	30.0	Sand, coarse, moderately			
		sorted, rounded, some			
		gravel, wet			
Flush Mount Waiver granted on 10-1-92 for Johnson Control, Inc by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-2-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 10-7-92 under the business name of Geotechnical Services, Inc by (signature) Allison Irwin					