

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SE 1/4 NW 1/4 SW 1/4		Section Number 36	Township Number T 27 S	Range Number R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 175' Southwest of 1919 Southwest Boulevard, Wichita, KS				52905003		MW-2
2 WATER WELL OWNER: Worldwide Construction Services RR#, St. Address, Box # : 1919 Southwest Boulevard City, State, ZIP Code : Wichita, KS 67213 Board of Agriculture, Division of Water Resources Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 19 ft. ELEVATION: Approx. Surface Elev.: 1300				
1 Mile		Depth(s) Groundwater Encountered 1. 12 ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL . 9.9 ft. below land surface measured on mo/day/yr . 01/11/90				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield . N/A gpm: Well water was ft. after hours pumping gpm				
Bore Hole Diameter . 9 in. to 19.5 ft., and in. to ft.		WELL WATER TO BE USED AS:				
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well				
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted						
Water Well Disinfected? Yes No X						
5 TYPE OF BLANK CASING USED:						
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped						
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded						
Blank casing diameter . 2 in. to 6.5 ft., Dia . in. to ft., Dia . in. to ft.						
Casing height above land surface . 3 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement						
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)						
12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)						
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes						
7 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From 6.5 ft. to 19 ft., From ft. to ft.						
From ft. to ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 5.5 ft. to 19.5 ft., From ft. to ft.						
From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 0 ft. to 3.5 ft., From 3.5 ft. to 5.5 ft., From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)						
13 Insecticide storage Removed fuel tank excavation						
Direction from well? S How many feet? 190						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	2.0	Fill: Dark Brown Lean Clay				
2.0	6.5	Light Gray-Brown Fat Clay				
6.5	8.0	Gray-Brown Lean to Fat Clay				
8.0	17.5	Light Brown Fine to Medium Sand				
17.5	19.5	Light Brown Medium to Coarse Sand				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01/11/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 2/16/99 under the business name of Terracon Consultants, Inc. by (signature)						