


1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SE 1/4 SW 1/4 NW 1/4		Section Number 36	Township Number T 27 S	Range Number R 1 E/W																																																																														
Distance and direction from nearest town or city street address of well if located within city? Northwest Corner of May and Lessler Streets, Wichita, Kansas 01948012 MW-1																																																																																				
2 WATER WELL OWNER: Hallum Tooling RR#, St. Address, Box #: 3838 May Street City, State, ZIP Code: Wichita, Kansas 67213 Board of Agriculture, Division of Water Resources Application Number:																																																																																				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION: Approx. Surface Elev.: 1299.3 Depth(s) Groundwater Encountered 1. 15 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 13.5 ft. below land surface measured on mo/day/yr 05/11/94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 8.25 in. to 65 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X																																																																																		
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued.....Clamped..... 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded..... Blank casing diameter 2 in. to 10 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface: 3 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 10 ft. to 65 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 3 ft. to 65 ft., From ft. to ft. From ft. to ft., From ft. to ft.																																																																																				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0.0 ft. to 1.0 ft., From 1.0 ft. to 3.0 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet?																																																																																				
<table border="1" style="width:100%; border-collapse: collapse;"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0.0</td><td>1.5</td><td>Fill: Sandy Gravel With Roots and Lean Clay</td><td></td><td></td><td></td></tr><tr><td>1.5</td><td>4.0</td><td>Lean Clay</td><td></td><td></td><td></td></tr><tr><td>4.0</td><td>6.0</td><td>Sandy Lean Clay; Gray</td><td></td><td></td><td></td></tr><tr><td>6.0</td><td>8.0</td><td>Silty Lean Clay; Brown</td><td></td><td></td><td></td></tr><tr><td>8.0</td><td>11.0</td><td>Lean Clay; Brown</td><td></td><td></td><td></td></tr><tr><td>11.0</td><td>13.0</td><td>Silty Lean Clay; Light Gray</td><td></td><td></td><td></td></tr><tr><td>13.0</td><td>16.0</td><td>Silty Lean Clay; Light Gray to Brown, With Some Gravel</td><td></td><td></td><td></td></tr><tr><td>16.0</td><td>23.0</td><td>Fine Sand; Brown; Wet</td><td></td><td></td><td></td></tr><tr><td>23.0</td><td>33.0</td><td>Fine to Coarse Sand; Brown, With Silt Seams</td><td></td><td></td><td></td></tr><tr><td>33.0</td><td>48.0</td><td>Fine to Coarse Sand; Very Wet</td><td></td><td></td><td></td></tr><tr><td>48.0</td><td>57.0</td><td>Fine to Coarse Sand, With Some Clay</td><td></td><td></td><td></td></tr><tr><td>57.0</td><td>65.0</td><td>Shale; Gray; Stiff</td><td></td><td></td><td></td></tr></tbody></table>							FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0.0	1.5	Fill: Sandy Gravel With Roots and Lean Clay				1.5	4.0	Lean Clay				4.0	6.0	Sandy Lean Clay; Gray				6.0	8.0	Silty Lean Clay; Brown				8.0	11.0	Lean Clay; Brown				11.0	13.0	Silty Lean Clay; Light Gray				13.0	16.0	Silty Lean Clay; Light Gray to Brown, With Some Gravel				16.0	23.0	Fine Sand; Brown; Wet				23.0	33.0	Fine to Coarse Sand; Brown, With Silt Seams				33.0	48.0	Fine to Coarse Sand; Very Wet				48.0	57.0	Fine to Coarse Sand, With Some Clay				57.0	65.0	Shale; Gray; Stiff			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																																															
0.0	1.5	Fill: Sandy Gravel With Roots and Lean Clay																																																																																		
1.5	4.0	Lean Clay																																																																																		
4.0	6.0	Sandy Lean Clay; Gray																																																																																		
6.0	8.0	Silty Lean Clay; Brown																																																																																		
8.0	11.0	Lean Clay; Brown																																																																																		
11.0	13.0	Silty Lean Clay; Light Gray																																																																																		
13.0	16.0	Silty Lean Clay; Light Gray to Brown, With Some Gravel																																																																																		
16.0	23.0	Fine Sand; Brown; Wet																																																																																		
23.0	33.0	Fine to Coarse Sand; Brown, With Silt Seams																																																																																		
33.0	48.0	Fine to Coarse Sand; Very Wet																																																																																		
48.0	57.0	Fine to Coarse Sand, With Some Clay																																																																																		
57.0	65.0	Shale; Gray; Stiff																																																																																		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05/11/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 05/11/94 under the business name of Terracon Consultants, Inc. by (signature) <i>Steve Fischer</i>																																																																																				
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																																																				

OFFICE USE ONLY

T

R

E/W

SEC.

1/4

1/4

1/4