

1 LOCATION OF WATER WELL: Sedgwick		FRACTION <i>SE SE SW NW</i> <i>SE</i> 1/4 <i>NW</i> 1/4 <i>NE</i> 1/4		Section Number <i>22</i>	Township Number T <i>27</i> S	Range Number <i>22</i> 1 West R <i>22</i> E/W
--	--	--	--	-----------------------------	----------------------------------	---

Distance and direction from nearest town or city street address of well if located within city?

6801 Par Lane Wichita, Kansas

2	WATER WELL OWNER:	REMINGTON APARTMENTS	
	RR#, ST. ADDRESS, BOX #:	1222 ST. Andrews Drive	Board of Agriculture, Division of Water Resource
	CITY, STATE, ZIP CODE:	Wichita, Kansas	67230 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 110 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON 08/15/1994 Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm Bore Hole Diameter 12 in. to 110 ft. and _____ in. to _____ ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes _____ No X ; If yes, mo/day/yr sample was submitted _____ Water Well Disinfected? Yes X No _____
---	--

5 TYPE OF CASING USED:		5 Wrought iron		8 Concrete tile		CASING JOINTS:		Glued ☒ Clamped	
1 Steel		6 Asbestos-Cement		9 Other (Specify below)				Welded	
2 PVC		7 Fiberglass		SDR-26				Threaded	
Blank casing Diameter 8 in. to 50		ft., Dia		in. to		ft., Dia		in. to	
Casing height above land surface 12 in.		weight 2.35		lbs. / ft.		Wall thickness or gauge No.		.214	
TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Fiberglass		7 PVC		10 Asbestos-cement			
1 Steel		3 Stainless Steel		8 RMP (SR)		11 other (specify)			
2 Brass		4 Galvanized steel		9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped		8 Saw cut		11 None (open hole)			
1 Continous slot		6 Wire wrapped		9 Drilled holes					
2 Louvered shutter		7 Torch cut		10 Other (specify)					
4 Key punched									
SCREEN-PERFORATION INTERVALS:		from 50		ft. to 70		ft., From		ft. to	
		from		ft. to		ft., From		ft. to	
GRAVEL PACK INTERVALS:		from 24		ft. to 110		ft., From		ft. to	
		from		ft. to		ft., From		ft. to	

6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 4 ft. to 24 ft.			ft. From	ft. to	ft. From
What is the nearest source of possible contamination:					ft. to
1 Septic tank	4 Lateral lines	7 Pit privy		10 Livestock pens	14 Abandon water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon		11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard		12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	None Apparent
Direction from well?					How many feet?

[illegible]

7. CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08/15/1994 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 08/17/94 Under the business name of Harp Well & Pump Service, Inc by (signature) Jane Frederick