

MNH # 11

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4

1/4

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgewick</u>		<u>NE 1/4 NE 1/4 NW 1/4</u>	<u>21</u>	<u>T 27 S</u>	<u>R 1 E 10</u>
Distance and direction from nearest town or city street address of well if located within city? <u>8101 W Central Wichita KS</u>					
2 WATER WELL OWNER: <u>Finn Oil & Chemical Co.</u>					
RR# St. Address, Box # : <u>PO Box 2159</u>			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : <u>Dallas TX</u>			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>41</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>7 1/4</u> in. to ft., and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ☒ Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes ☒ No ☒					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
☒ PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded ☒
Blank casing diameter in. to <u>26</u> ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface in., weight <u>Sched 40</u> lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		☒ Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From <u>26</u> ft. to <u>41</u> ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>41</u> ft. to <u>24</u> ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement ☒ Cement grout 3 Bentonite 4 Other					
Grout Intervals: From <u>23</u> ft. to <u>0.6</u> ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	☒ Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? <u>North/East</u>				13 Insecticide storage	
				How many feet? <u>105'</u>	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3'	Topsoil			
3'	5'	Brown Clay			
5'	10'	Brown Clay			
10'	15'	Brown tan Clay			
15'	20'	Tan Brown Clay w FINE Sand			
20'	25'	FINE Grained Sand			
25'	30'	FINE to MED Grained Sand			
30'	35'	MED Grained Sand			
35'	41'	MED to COARSE Sand w/Gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-29-94</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>575</u> This Water Well Record was completed on (mo/day/yr) <u>8-4-94</u> under the business name of <u>Kurtz Environmental Service</u> by (signature) <u>[Signature]</u>					