

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		NE 1/4 SE 1/4 NE 1/4	25	T 27 S	R 1 <u>WEST</u>
Distance and direction from nearest town or city street address of well if located within city? <u>851 South Meridian, Wichita, Kansas</u>					
2 WATER WELL OWNER:		01948024		MW-1	
RR#, St. Address, Box # :		P.O. Box 17087		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code :		Wichita, Kansas 67217		Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 18.5 ft. ELEVATION: Approx. 1300.0			
		Depth(s) Groundwater Encountered 1. 13.0 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 14.76 ft. below land surface measured on mo/day/yr 09/29/94			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: 8.25 in. to 18.5 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		Casing Joints: Glued Clamped Welded Threaded <u>X</u>			
1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter 2 in. to 8.5 ft. Dia in. to ft. Dia in. to ft.		Casing height above land surface -3 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS			
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 8.5 ft. to 10 ft. From ft. to ft. From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS:		From 6.5 ft. to 10 ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 0 ft. to 4.5 ft. From 4.5 ft. to 6.5 ft. From ft. to ft.		What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) <u>UST</u> 13 Insecticide storage			
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	1.0	Brown, Silty Fine Sand			
1.0	3.5	Brown, Sandy Fat Clay			
3.5	8.5	Gray Fat Clay			
8.5	13.5	Gray Clayey Sand			
13.5	18.5	Gray, Fine to Coarse Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09/07/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 09-27-94 under the business name of Terracon Consultants, Inc. by (signature) <i>Steve Fischer</i>					