

1 LOCATION OF WATER WELL: Fraction NE 1/4 NW 1/4 SE 1/4 Section Number 13 Township Number T 27 S Range Number R 1 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city? See Below

2 WATER WELL OWNER: Dave Thirsk
 RR#, St. Address, Box #: 918 N. St. Paul
 City, State, ZIP Code: Wichita, KS 67203
 Board of Agriculture, Division of Water Resources
 Application Number: 30

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
	NW	NE	
		X	
	SW	SE	
W			E
			S

4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: 10-27-94
 Depth(s) Groundwater Encountered 1. 15 ft. 2. 10-27-94 ft. 3. 10-27-94 ft.
 WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 15 ft. after 10-27-94 hours pumping 10-27-94 gpm
 Est. Yield 15 gpm: Well water was 15 ft. after 10-27-94 hours pumping 10-27-94 gpm
 Bore Hole Diameter 15 in. to 10-27-94 ft., and 10-27-94 in. to 10-27-94 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
☒ 1 Steel ☐ 3 RMP (SR) ☐ 6 Asbestos-Cement ☐ 9 Other (specify below)
☐ 2 PVC ☐ 4 ABS ☐ 7 Fiberglass
 Blank casing diameter 3 in. to 10-27-94 ft., Dia. 10-27-94 in. to 10-27-94 ft., Dia. 10-27-94 in. to 10-27-94 ft.
 Casing height above land surface 0 in., weight 10-27-94 lbs./ft. Wall thickness or gauge No. 10-27-94
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 8 RMP (SR) ☐ 11 Other (specify)
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☐ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐ 10 Other (specify) NA
☐ 7 Torch cut ☐ 10 Other (specify) NA
 SCREEN-PERFORATED INTERVALS: From NA ft. to NA ft., From NA ft. to NA ft., From NA ft. to NA ft.
 GRAVEL PACK INTERVALS: From NA ft. to NA ft., From NA ft. to NA ft., From NA ft. to NA ft.

6 GROUT MATERIAL: ☒ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other
 Grout Intervals: From 8 ft. to 10 ft., From 10 ft. to 10-27-94 ft., From 10-27-94 ft. to 10-27-94 ft.
 What is the nearest source of possible contamination:
☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage
 Direction from well? West How many feet? 5

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		<u>2nd well</u>	<u>8</u>	<u>10</u>	<u>cement</u>
			<u>10</u>	<u>30</u>	<u>gravel</u>

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-27-94 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 10-31-94
 under the business name Weninger Drilling by (signature) Karina Morrissey