

1 LOCATION OF WATER WELL: Fraction NW 1/4 SW 1/4 SW 1/4 Section Number 19 Township Number 27 Range Number 1 County Sedgwick Distance and direction from nearest town or city street address of well if located within city? See Below

2 WATER WELL OWNER: John Torrez Board of Agriculture, Division of Water Resources Application Number: 7-1-94

RR#, St. Address, Box #: 1372 Pine Grove Ct. City, State, ZIP Code: Wichita, KS 67209

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
	NW	NE	
W			E
	SW	SE	
S			

1 Mile

4 DEPTH OF COMPLETED WELL: 96 ft. ELEVATION: 25 ft. below land surface measured on mo/day/yr 7-1-94

Depth(s) Groundwater Encountered 25 ft. 2. 20 ft. 3. 20 ft.

WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr 7-1-94

Pump test data: Well water was 20 ft. after 1/2 hours pumping 20 gpm

Est. Yield 40 gpm: Well water was 96 ft. after 1/2 hours pumping 20 gpm

Bore Hole Diameter: 11 in. to 96 ft. and 96 in. to 96 ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded

Blank casing diameter 5 in. to 12 ft., Dia. 2.60 in. to 100 PSI ft., Dia. 100 PSI in. to 100 PSI ft.

Casing height above land surface 12 in., weight 2.60 lbs./ft. Wall thickness or gauge No. 100 PSI

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 81 ft. to 96 ft., From 25 ft. to 96 ft., From 25 ft. to 96 ft., From 25 ft. to 96 ft., From 25 ft. to 96 ft., From 25 ft. to 96 ft.

GRAVEL PACK INTERVALS: From 25 ft. to 96 ft., From 25 ft. to 96 ft., From 25 ft. to 96 ft., From 25 ft. to 96 ft., From 25 ft. to 96 ft., From 25 ft. to 96 ft.

6 GROUT MATERIAL: 3 1 Neat cement 25 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 25 ft., From 25 ft. to 96 ft., From 25 ft. to 96 ft., From 25 ft. to 96 ft., From 25 ft. to 96 ft., From 25 ft. to 96 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? East How many feet? 30 ft

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil	84	93	gravel
2	17	Clay			
17	38	gravel			
38	84	Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-1-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 7-27-94 under the business name of Weninger Drilling by (signature) Karina Morrissey

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.