

1 LOCATION OF WATER WELL:	FRACTION	Section Number	Township Number	Range Number	
Sedgwick	SE 1/4 SW 1/4 SW 1/4	3	T 27 S	R 1W E/W	
Distance and direction from nearest town or city street address of well if located within city?					
Ridge Road off of 21st St. N., North side Wichita, Kansas					
2 WATER WELL OWNER: CITY OF WICHITA					
RR#, ST. ADDRESS, BOX #: P.O. Box 19163					
CITY, STATE, ZIP CODE: Wichita, Kansas 67277					
Board of Agriculture, Division of Water Resource Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION:			
		Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.			
		WELL'S STATIC WATER LEVEL 8 FT. BELOW LAND SURFACE MEASURED ON 10/21/1994			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter in. to ft. and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well		2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below)			
10 Monitoring well		Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ If yes, mo/day/yr sample was submitted			
Water Well Disinfected? Yes ☒ No					
5 TYPE OF CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (Specify below) Welded					
Blank casing Diameter 8 in. to ft., Dia in. to ft., Wall thickness or gauge No.					
Casing height above land surface 36 in., weight lbs. / ft.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENING ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
3 Torch cut 10 Other (specify)					
SCREEN-PERFORATION INTERVALS: from ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: from ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 3 ft. to 9 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage None Apparent					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			0	3	surface clays and silts
			3	9	cement grout
			9	15	bentonite hole plug
			15	40	chlorinated sand and gravel
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/21/1994 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 10/24/94 Under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Jane Frederick</i>					