


1 LOCATION OF WATER WELL: Sedgwick	FRACTION SE 1/4 SW 1/4 SW 1/4	Section Number 3	Township Number T 27 S	Range Number R 1W E/W					
Distance and direction from nearest town or city street address of well if located within city? 1/4 E. of Ridge Road off of 21st St. N., North side Wichita, Kansas									
2 WATER WELL OWNER: CITY OF WICHITA RR#, ST. ADDRESS, BOX #: P.O. Box 19163 CITY, STATE, ZIP CODE: Wichita, Kansas 67277 Board of Agriculture, Division of Water Resource Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 8 FT. BELOW LAND SURFACE MEASURED ON 10/21/1994 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No								
	5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (Specify below) Welded 7 Fiberglass Threaded Blank casing Diameter 8 in. to ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 36 in., weight lbs. / ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
	SCREEN-PERFORATION INTERVALS: from ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: from ft. to ft., From ft. to ft.								
	6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 9 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandon water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent Direction from well? How many feet?								
FROM	TO	LITHOLOGIC LOG			FROM	TO	PLUGGING INTERVALS		
					0	3	surface clays and silts		
					3	9	cement grout		
					9	15	bentonite hole plug		
					15	40	chlorinated sand and gravel		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/21/1994 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 10/24/94 Under the business name of Harp Well & Pump Service, Inc by (signature) <i>Jane Frederick</i>									