

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SW ¼ SW ¼ SW ¼		15		T 27 S		R 1 EW	
Distance and direction from nearest town or city street address of well if located within city?									
Town & Country Market, 731 North Ridge Road, Wichita, Kansas									
2 WATER WELL OWNER:		Town & Country Markets				01948034 MW-4			
RR#, St. Address, Box # :		P.O. Box 17087				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Wichita, Kansas 67217				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 17.0 ft. ELEVATION: 1315.85							
		Depth(s) Groundwater Encountered 1. 11.5 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 11.20 ft. below land surface measured on mo/day/yr 10/27/94							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 8.25 in. to 17 ft. and in. to ft.							
		WELL WATER TO BE USED AS:							
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No X							
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped							
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile Welded							
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) Threaded X							
Blank casing diameter 2 in. to 7 ft. Dia		in. to ft. Dia							
Casing height above land surface -3 in., weight		lbs./ft. Wall thickness or gauge No. Schedule 40							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS:		From 7.0 ft. to 17.0 ft. From ft. to ft.							
GRAVEL PACK INTERVALS:		From 5.0 ft. to 17.0 ft. From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 0 ft. to 3 ft. From 3 ft. to 5 ft. From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) UST									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well?		How many feet?							
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
0.0	0.5	Grass							
0.5	2.0	Dark Brown, Sandy, Lean to Fat Clay							
2.0	9.0	Gray, Sandy, Lean to Fat Clay							
9.0	17.0	Brown, Fine to Coarse Sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/21/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 11-14-94 under the business name of Terracon Consultants, Inc. by (signature) Steve Fischer									