

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SE 1/4 SE 1/4 SE 1/4		16		T 27 S		R 1 EW	
Distance and direction from nearest town or city street address of well if located within city?									
Town & Country Market, 731 North Ridge Road, Wichita, Kansas									
2 WATER WELL OWNER:		Town & Country Markets				01948034 MW-3			
RR#, St. Address, Box # :		P.O. Box 17087				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Wichita, Kansas 67217				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 18.0 ft. ELEVATION: 1317.40							
		Depth(s) Groundwater Encountered 1. 13.0 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 12.54 ft. below land surface measured on mo/day/yr 10/27/94							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 8.25 in. to 18 ft. and in. to ft.							
WELL WATER TO BE USED AS:									
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)									
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well									
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes No X									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded									
2 PVC 4 ABS 7 Fiberglass Threaded X									
Blank casing diameter 2 in. to 8 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface -3 in. weight lbs./ft. Wall thickness or gauge No. Schedule 40									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 8.0 ft. to 18.0 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 6.0 ft. to 18.0 ft. From ft. to ft.									
6 GROUT MATERIAL:									
1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0 ft. to 4 ft. From 4 ft. to 6 ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage UST									
Direction from well? How many feet?									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0.0 0.5 Asphalt									
0.5 3.0 Brown and Red-Brown, Sandy, Lean to Fat Clay									
3.0 6.0 Gray, Sandy, Lean to Fat Clay									
6.0 9.0 Gray, Sandy Fat Clay									
9.0 18.0 Gray-Brown, Fine to Medium Sand									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/18/94 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 11-16-94									
under the business name of Terracon Consultants, Inc. by (signature) Steve Fischer									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									