

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SE 1/4 SE 1/4 SE 1/4		16		T 27 S		R 1 EW	
Distance and direction from nearest town or city street address of well if located within city?									
Town and Country Market, 731 North Ridge Road, Wichita, Kansas									
2 WATER WELL OWNER: Town and Country Markets						01948034 MW-1			
RR#, St. Address, Box # : P.O. Box 12087						Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Wichita, Kansas 67217						Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:				4 DEPTH OF COMPLETED WELL: 20 ft. ELEVATION: 1320.67					
				Depth(s) Groundwater Encountered 1. 15.0 ft. 2. ft. 3. ft.					
				WELL'S STATIC WATER LEVEL 15.23 ft. below land surface measured on mo/day/yr 10/27/94					
				Pump test data: Well water was ft. after hours pumping gpm					
				Est. Yield N/A gpm: Well water was ft. after hours pumping gpm					
				Bore Hole Diameter 8.25 in. to 20 ft., and in. to ft.					
				WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
				1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
				2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
				Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted					
				Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:				CASING JOINTS: Glued Clamped					
1 Steel 3 RMP (SR)				Welded					
2 PVC 4 ABS				Threaded X					
5 Wrought iron 8 Concrete tile									
6 Asbestos-Cement 9 Other (specify below)									
7 Fiberglass									
Blank casing diameter 2 in. to 10 ft., Dia				in. to ft., Dia					
Casing height above land surface -3 in., weight				lbs./ft. Wall thickness or gauge No. Schedule 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:				7 PVC 10 Asbestos-cement					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)				11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS				12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:				8 Saw cut 11 None (open hole)					
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 8 ft. to 20 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0 ft. to 6 ft., From 6 ft. to 8 ft., From ft. to ft.									
What is the nearest source of possible contamination:				10 Livestock pens 14 Abandoned water well					
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)				UST					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well?				How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
0.0	0.4	Asphalt							
0.4	2.0	Dark Brown, Sandy, Lean to Fat Clay							
2.0	3.0	Red-Brown, Sandy, Lean to Fat Clay							
3.0	9.0	Dark Brown, Sandy Fat Clay							
9.0	14.0	Dark Gray, Sandy, Lean to Fat Clay							
14.0	20.0	Brown, Fine to Coarse Sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/18/94 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 11-16-94									
under the business name of Terracon Consultants, Inc. by (signature) Steve Fischer									