


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: SEDGWICK	SW 1/4 SW 1/4 SW 1/4	24	T 27 S	R 1 EW

Distance and direction from nearest town or city street address of well if located within city?

240 S WEST ST., WICHITA, KS

MW - 01

2 WATER WELL OWNER: TOWN & COUNTRY	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : 240 S WEST ST.	Application Number:
City, State, ZIP Code : WICHITA, KS 67201	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 20 ft. ELEVATION: 1305.14
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL: 1290.99 ft. below land surface measured on mo/day/yr 4/1/94
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter: 7.75 in. to 20 ft. and in. to ft.
	WELL WATER TO BE USED AS:
	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	3 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	7 Fiberglass		Threaded. X
Blank casing diameter: 2 in. to 10 ft. Dia			
Casing height above land surface: NA in. weight			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	8 RMP (SR)	11 Other (specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless steel			
4 Galvanized steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 10 ft. to 19.5 ft.			
GRAVEL PACK INTERVALS: From 8 ft. to 20 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 6 ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.5'	ASPHALT W/ GRAVEL FILL BASE	14'	15.5'	GRADING WET
.5'	3'	CLAYEY SILT, BLACK, PETROLEUM ODOR, SLIGHTLY STIFF, MOIST W/ FRACTURES, (ALLUVIUM)	15.5'	20'	GRADING W/ PEBBLE SIZED GRAVEL
3'	6'	SILTY CLAY, DARK BROWN, PETROLEUM ODOR, STIFF, MOIST, LOW PLASTICITY, W/ TRACE SAND (ALLUVIUM)			
6'	8.5'	SILTY SAND, BROWN, PETROLEUM ODOR, FINE GRAINED, ANGULAR TO ROUNDED, SORTED, MOIST (ALLUVIUM)			
8.5'	12.5'	SAND, BROWN, VERY STRONG PETROLEUM ODOR, FINE TO MED. GRAINED, ANGULAR TO ROUNDED, POORLY SORTED, MOIST, (ALLUVIUM)			
12.5'	14'	GRADING GRAY & VERY COARSE GRAINED			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/28/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 549 This Water Well Record was completed on (mo/day/yr) 3/28/94 under the business name of J & R DRILLING SERVICES, INC. by (signature) Raymond Corns
