

1 LOCATION OF WATER WELL:		FRACTION		Section Number		Township Number		Range Number	
Sedgwick 087		NE 1/4 SE 1/4 NE 1/4		35		T 27 S		R 1W E/W	
Distance and direction from nearest town or city street address of well if located within city?									
Intersection of West and Esthner Streets Wichita, Kansas									
2 WATER WELL OWNER:		CITY OF WICHITA				Board of Agriculture, Division of Water Resource			
RR#, ST. ADDRESS, BOX #:		P.O. Box 9163				Application Number: 940497			
CITY, STATE, ZIP CODE:		Wichita, Kansas 67277							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL		40 ft.		ELEVATION:			
		Depth(s) groundwater Encountered		1 ft.		2 ft.		3 ft.	
		WELL'S STATIC WATER LEVEL		12		FT. BELOW LAND SURFACE MEASURED ON		01/13/1995	
		Pump test data:		Well water was		ft. after		hours pumping	
		Est. Yield		gpm: Well water was		ft. after		hours pumping	
		Bore Hole Diameter		12 in. to 40		ft. and		in. to	
WELL WATER TO BE USED AS:		5 Public water supply		8 Air conditioning		11 Injection well			
1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering		12 Other (Specify below)	
2 Irrigation		4 Industrial		7 Lawn and garden only		10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes		No		X		If yes, mo/day/yr sample was submitted			
5 TYPE OF CASING USED:		5 Wrought iron		8 Concrete tile		CASING JOINTS:		Glued X Clamped	
1 Steel		3 RMP (SR)		6 Asbestos-Cement		9 Other (Specify below)		Welded	
2 PVC		4 ABS		7 Fiberglass		SDR-26		Threaded	
Blank casing Diameter		8 in. to 20		ft., Dia		in. to		ft.	
Casing height above land surface		12 in.,		weight 5.541		lbs. / ft.		Wall thickness or gauge No. .322	
TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Fiberglass		7 PVC		10 Asbestos-cement			
1 Steel		3 Stainless Steel		8 RMP (SR)		11 other (specify)			
2 Brass		4 Galvanized steel		9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped		8 Saw cut		11 None (open hole)			
1 Continuous slot		3 Mill slot		6 Wire wrapped		9 Drilled holes			
2 Louvered shutter		4 Key punched		7 Torch cut		10 Other (specify)			
SCREEN-PERFORATION INTERVALS:		from 20		ft. to 40		ft., From		ft. to	
GRAVEL PACK INTERVALS:		from 20		ft. to 40		ft., From		ft. to	
6 GROUT MATERIAL:		1 Neat cement		2 Cement grout		3 Bentonite		4 Other bentonite hole plug	
Grout Intervals: From 0		ft. to 20		ft. From		ft. to		ft. From	
What is the nearest source of possible contamination:		1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage		14 Abandon water well	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage		15 Oil well/Gas well	
Direction from well? Northeast						13 Insecticide storage		16 Other (specify below)	
Direction from well?		Northeast		How many feet? 12					
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS			
0	4	topsoil							
4	18	fine silty sand							
18	20	tan clay							
20	40	medium sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01/13/1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 01/25/95 Under the business name of Harp Well & Pump Service, Inc. by (signature) Jane Frederick									