

1 LOCATION OF WATER WELL: County: <u>SEDGWICK</u>	Fraction <u>NW</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$	Section Number <u>28</u>	Township Number T <u>27</u> S	Range Number R <u>1</u> E <u>(W)</u>
--	---	-----------------------------	----------------------------------	---

Distance and direction from nearest town or city street address of well if located within city?

MW-295

2 WATER WELL OWNER: RR#, St. Address, Box # City, State, ZIP Code	<u>Leangit Way</u> <u>One Leangit Way</u> <u>Wichita, KS 67209</u>	Board of Agriculture, Division of Water Resources Application Number:
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>43.5</u> ft. ELEVATION:
--	--

	Depth(s) Groundwater Encountered <u>35.21</u> ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>35.21</u> ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter <u>8</u> in. to <u>43.5</u> ft., and in. to ft.	
WELL WATER TO BE USED AS:	
1 Domestic	5 Public water supply
2 Irrigation	6 Oil field water supply
3 Feedlot	7 Lawn and garden only
4 Industrial	8 Air conditioning
	9 Dewatering
	10 Monitoring well
	11 Injection well
	12 Other (Specify below)
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes No <u>X</u>

5 TYPE OF BLANK CASING USED:	3 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	7 Fiberglass		Threaded <u>X</u>
Blank casing diameter <u>2</u> in. to <u>27.5</u> ft. Dia in. to ft. Dia in. to ft.			
Casing height above land surface <u>30</u> in. weight <u>1.69</u> lbs./ft. Wall thickness or gauge No.			

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement
1 Steel	8 RMP (SR)	11 Other (specify)
2 Brass	9 ABS	12 None used (open hole)
3 Stainless steel		
4 Galvanized steel		
5 Fiberglass		
6 Concrete tile		

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			

SCREEN-PERFORATED INTERVALS:	From <u>27.5</u> ft. to <u>42.5</u> ft.	From ft. to ft.
	From ft. to ft.	From ft. to ft.
GRAVEL PACK INTERVALS:	From <u>24</u> ft. to <u>42.5</u> ft.	From ft. to ft.
	From ft. to ft.	From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other <u>Concrete pad</u>
Grout Intervals: From <u>3</u> ft. to <u>23</u> ft. From <u>23</u> ft. to <u>24</u> ft. From <u>0</u> ft. to <u>3</u> ft.				

What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well
1 Septic tank	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	13 Insecticide storage	
4 Lateral lines		
5 Cess pool		
6 Seepage pit		
7 Pit privy		
8 Sewage lagoon		
9 Feedyard		

Direction from well? <u>unknown</u>	How many feet?
-------------------------------------	----------------

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>1.5</u>	<u>Silt</u>			
<u>1.5</u>	<u>6.5</u>	<u>Sand</u>			
<u>6.5</u>	<u>12</u>	<u>Silt</u>			
<u>12</u>	<u>20</u>	<u>Sand</u>			
<u>20</u>	<u>20.5</u>	<u>Clay</u>			
<u>20.5</u>	<u>43.5</u>	<u>Sand</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>2-1-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>581</u> This Water Well Record was completed on (mo/day/yr) <u>2-24-95</u> under the business name of <u>Wayne, Inc.</u> by (signature) <u>Steven R. Mitchell</u>
--