

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>	Fraction <u>NW</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$	Section Number <u>23</u>	Township Number T <u>27</u> S	Range Number R <u>1</u> E <u>(W)</u>
--	---	-----------------------------	----------------------------------	---

Distance and direction from nearest town or city street address of well if located within city?

4932 West Central, Wichita

2 WATER WELL OWNER: RR#, St. Address, Box # City, State, ZIP Code	<u>QuikTrip Corp.</u> <u>901 N. Mingo</u> <u>Tulsa, OK 74116</u>	Board of Agriculture, Division of Water Resources Application Number:
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>19</u> ft. ELEVATION: <u>1311.15</u>
--	--

Depth(s) Groundwater Encountered 1 13 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 13.02 ft. below land surface measured on mo/day/yr 8/30/93

Pump test data: Well water was N/A ft. after hours pumping gpm

Est. Yield N/A gpm Well water was ft. after hours pumping gpm

Bore Hole Diameter 6.75 in. to 19 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well <u>PMW-1</u>

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
------------------------------	----------------	-----------------	--

1 Steel

2 PVC

Blank casing diameter 2 in. to 9 ft. Dia

Casing height above land surface 0 (Flush) in. weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

<u>1 Continuous slot</u>	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 7 ft. to 19 ft. From 7 ft. to 19 ft. From 7 ft. to 19 ft. From 7 ft. to 19 ft.

GRAVEL PACK INTERVALS: From 7 ft. to 19 ft. From 7 ft. to 19 ft. From 7 ft. to 19 ft. From 7 ft. to 19 ft.

3 RMP (SR)

4 ABS

7 Fiberglass

Welded

Threaded

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	<u>3 Bentonite</u>	4 Other
-------------------	---------------	----------------	--------------------	---------

Grout Intervals: From 0 ft. to 1 ft. From 1 ft. to 7 ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	<u>16 Other (specify below)</u>
			13 Insecticide storage	<u>Former UST</u>

Direction from well? NE How many feet? 60'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>4.5</u>	<u>Asphalt</u>			
<u>4.5</u>	<u>19</u>	<u>Silty sand</u>			
		<u>Sand: med- to coarse</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8/30/93</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>549</u> This Water Well Record was completed on (mo/day/yr) <u>8-30-93</u> under the business name of <u>JTR Drilling Services</u> by (signature) <u>Raymond [Signature]</u>
--