

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		NW 1/4 NW 1/4 NW 1/4	27	T 27 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? in town					
2 WATER WELL OWNER: 3G Convenience					
RR#, St. Address, Box #: 7125 W MAPLE MW1 mw. 2?					
City, State, ZIP Code: Wichita, KS Board of Agriculture, Division of Water Resources					
Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 40.25 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 29.73 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter in. to ft. and in. to ft.			
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ☒ Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☐ If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes ☒ No ☐					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped ☒ PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass ☒ Threaded					
Blank casing diameter 2 in. to 25 ft. Dia. in. to ft. Dia. in. to ft.					
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot ☒ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 25.0 ft. to 40.0 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 23.0 ft. to 40.0 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement ☒ Cement grout 3 Bentonite 4 Other					
Grout intervals: From 0 ft. to 1.0 ft. From 1.0 ft. to 21.0 ft. From 21.0 ft. to 23.0 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy ☒ Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Topsoil ORGANIC			
1	2.5	clay brown Sandy (F-M)			
2.5	4.0	Sand Brown Silt			
4.0	20.0	Clay BROWN Sandy (F-M)			
20.0	40.0	Sand (F-C) Red brown			
		silty moist at 25.0			
		wet at 30.0			
		Pebbles & GRAVEL at 25.0			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-23-94 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 493 This Water Well Record was completed on (mo/day/yr) 9/15/94					
under the business name of TEST by (signature) Clay P. Dyer					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4