


1 LOCATION OF WATER WELL: Fraction SW 1/4 NE 1/4 SE 1/4 Section Number 32 Township Number T 27 S Range Number R 10 E (W)  
 County: KINGMAN  
 Distance and direction from nearest town or city street address of well if located within city?  
100 W. 4th St. mw-4

2 WATER WELL OWNER: Gunningham USD #332  
 RR#, St. Address, Box #: Box 67  
 City, State, ZIP Code: Cunningham, KS 67035  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 29.5 ft. ELEVATION: 1702  
 Depth(s) Groundwater Encountered 1. 2.79 ft. 2. 22 ft. 3. - ft.  
 WELL'S STATIC WATER LEVEL 21.19 ft. below land surface measured on mo/day/yr 9-3-93  
 Pump test data: Well water was - ft. after - hours pumping - gpm  
 Est. Yield - gpm: Well water was - ft. after - hours pumping - gpm  
 Bore Hole Diameter 8 in. to 30' ft., and - in. to - ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well mw-4  
 Was a chemical/bacteriological sample submitted to Department? Yes - No x; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes - No (No)

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued - Clamped -  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded -  
 7 Fiberglass Threaded check  
 Blank casing diameter 2" in. to 29.5 ft., Dia - in. to - ft., Dia - in. to - ft.  
 Casing height above land surface -3.0 in., weight - lbs./ft. Wall thickness or gauge No. 40  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) -  
 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) -  
 SCREEN-PERFORATED INTERVALS: From 19.5 ft. to 29.5 ft., From - ft. to - ft.  
 GRAVEL PACK INTERVALS: From 30.0' ft. to 17.5' ft., From - ft. to - ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other -  
 Grout Intervals: From 0 ft. to 17.5 ft., From - ft. to - ft., From - ft. to - ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)  
 Direction from well? South East How many feet? 75

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.3'	TOPSOIL (GRASS)			
0.3'	7.5'	BROWN SANDY SILTY CLAY			
7.5'	10.0'	Grey Lt. BROWN SANDY SILTY CLAY			
10.0'	20.5'	BROWN MED-COARSE GRAIN SAND			
20.5'	22.5'	Grey Lt. BROWN SILTY CLAY			
22.5'	33.5'	Grey Lt. BROWN MED-COARSE GRAIN SAND			
	-TO-				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-1-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 410 This Water Well Record was completed on (mo/day/yr) 2-9-94 under the business name of Terracon Consultants Inc by (signature) Richard D. Murphy