		RECORD Form WWC-5	Division of Water Resources; App. No.
1 LOC	ATION OF	WATER WELL: Fraction	Section Number Township Number Range Number
County:	and direction	n from nearest town or city street address of well	4 32 T 27 S R 10W E/W If Global Positioning System (decimal degrees, min. of 4 digits)
located within city?  Latitude: N 37.65065°			
100 W. 4 <sup>th</sup> St. Cunningham, KS 67035 Longitude: W 98.43256°			
2 WATER WELL OWNER:			Elevation: 1697.95 RIM, 1697.62 TOC
	St. Address,		Datum: above mean sea level
City,	State, ZIP C	ode :	Data Collection Method: legal survey
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 30 ft.			
1	ATON	N Double (a) Commission Francisco de la companya della companya de la companya della companya de	MW13
ı	H AN "X" I	N Depth(s) Groundwater Encountered !	ft. 2 ft. 3 ft.
SEC	TION BOX:		22 ft. below land surface measured on mo/day/yr 8/15/07
	N : 1 :	Pump test data: Well water was	ft. after hours pumping gpm
		Est. Yield gpm: Well water was	ft. after hours pumping gpm
	W-+-NE-	1 Domestic 2 Feed lot 6 Oil field water	lic water supply 8 Air conditioning 11 Injection well r supply 9 Dewatering 12 Other (Specify below)
w	<del>                                     </del>	E 2 Irrigation 4 Industrial 7 Domestic (law	vn & garden) (10) Monitoring well
L	ws.x-	2 migation 4 moustrial / Domestic (lav	in & garden) (to) wonton to ring wen
l F	w- <del> -</del> s.x-	Was a chemical/bacteriological sample sub	mitted to Department? Yes No X; If yes, mo/day/yrs
ļ L	<u> </u>	Sample was submitted	Water Well Disinfected? Yes No X
5 TYP	E OF CASII	NG USED: 5 Wrought Iron 8 C	oncrete tile CASING JOINTS: Glued Clamped
	teel	3 RMP (SR) 6 Asbestos-Cement 9 C	ther (specify below) Welded
(2) P	VC	4 ABS 7 Fiberglass	Threaded X
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  2 PVC 4 ABS 7 Fiberglass Threaded X  Blank casing diameter 2 in. to 15 ft., Dia in. to ft., Dia in. to ft.  Casing height below land surface 0.33 ft., Weight Ibs./ft. Wall thickness or gauge No.  TYPE OF SCREEN OR PERFORATION MATERIAL:			
Casing height below land surface 0.33 ft., Weight lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 APS 11 Other (specific)			
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot 3 Mill slot 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  SCREEN-PERFORATED INTERVALS: From 15 ft. to 30 ft. From ft. to ft.  From ft. to ft. From ft. to ft.  GRAVEL PACK INTERVALS: From 13 ft. to 30 ft. From ft. to ft.  From ft. to ft. From ft. to ft.			
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)			
SCREE	N-PERFORA	TED INTERVALS: From 15 ft.	to 30 ft. From ft. to ft.
	DANEE DAA	From II.	10 II. From II. 10 II.
0	KAVEL PA	CK INTERVALS: FROM 15 II.	10 30 II. FIOID II. 10
From 11. 10 11. 17 II. 10 11.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other concrete, 0-3' Grout Intervals From 3 ft. to 13 ft. From ft. to ft. From ft. to ft.			
Grout Intervals From 3 ft. to 13 ft. From ft. to ft. From ft. to ft.			
What is the nearest source of possible contamination:			
	ptic tank		ivestock pens 13 Insecticide Storage 16 Other (specify
2 Sewer lines 5 Cess pool 8 Sewage lagoon (1) Fuel storage 14 Abandoned water well below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard Direction from well? SW  12 Fertilizer storage 15 Oil well/ gas well How many feet? 418			
			7
FROM			ROM TO PLUGGING INTERVALS
2	6	Topsoil   Silty-clay, red-brown, w/ limestone chips	
6	7	Silty-clay, buff, moist	
7	9	Clay, red-brown, moist, w/ limestone	
		chips	
9	29	As above, silty-clay only, fat, plastic,	
		moist	
29	30	Sand, very fine, flowing	FI - L
			Flushmount waiver from BOW
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged			
under my jurisdiction and was completed on (mo/day/year) 7/18/07 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 757 . This Water Well Record was completed on (modday/year) 8/22/07			
under the business name of Larsen & Associates, Inc. by (signature)			
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Nealth and Environment. Bureau of Water. Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to Water WER WELL OWNER and retain one for			
your reco	ds. Fee of \$5.0	V Jackson St., Suite 420, Topeka, Kansas 66612-1367. Tele O for each <u>constructed</u> well. Visit us at http://www.kdheks.g	onone 185-296-3522. Send one to wa rek WELL OWNER and retain one for ov/waterwell.