


1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 SW 1/4 Section Number 16 Township Number T 27 S Range Number R 12 E
 County: Pratt

Distance and direction from nearest town or city street address of well if located within city?
2 1/8 north, 4 1/2 east of Pratt, Ks.

2 WATER WELL OWNER: Ramblin Rose Ranch
 RR#, St. Address, Box #: Box 869 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Pratt, Ks. 67124 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 120 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 46 ft. 2. 11-6-98 ft. 3. 98 ft.
 WELL'S STATIC WATER LEVEL 46 ft. below land surface measured on mo/day/yr 11-6-98
 Pump test data: Well water was na ft. after na hours pumping na gpm
 Est. Yield na gpm: Well water was na ft. after na hours pumping na gpm
 Bore Hole Diameter 9 in. to 120 ft., and na in. to na ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well live stock
 Was a chemical/bacteriological sample submitted to Department? Yes na No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes na No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped na
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded na
 7 Fiberglass Threaded na
 Blank casing diameter 5 in. to 100 ft., Dia. na in. to na ft., Dia. na in. to na ft.
 Casing height above land surface 2 ft. in., weight SDR 26 lbs./ft. Wall thickness or gauge No. na
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) na
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) na
 SCREEN-PERFORATED INTERVALS: From 100 ft. to 120 ft., From na ft. to na ft.
 From na ft. to na ft., From na ft. to na ft.
 GRAVEL PACK INTERVALS: From 120 ft. to 20 ft., From na ft. to na ft.
 From na ft. to na ft., From na ft. to na ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug
 Grout Intervals: From 20 ft. to 0 ft., From na ft. to na ft., From na ft. to na ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) house
 13 Insecticide storage
 Direction from well? west How many feet? 1/2 mile

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil			
2	7	SAnd and gravel			
7	29	Brown & white clay			
29	41	Sand & gravel clean, coarse, loose			
41	57	Yellow brown, white & gray clay			
57	63	Sand & clay mixed			
63	108	Sand and gravel clean, coarse, & loose			
108	109	Brown clay			
109	120	Sand and gravel clean, coarse, loose			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-6-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 11-16-98 under the business name of Rosencrantz-Bemis by (signature) Freddie Rodson