


1 LOCATION OF WATER WELL: Fraction SW 1/4 SE 1/4 NE 1/4 Section Number 19 Township Number T 27 S Range Number R 12 xE/W
 County: Pratt

Distance and direction from nearest town or city street address of well if located within city?
2 3/4 east, 1 3/4 north of Pratt, Ks.

2 WATER WELL OWNER: John McGuire Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box # : 30212 NE 20
 City, State, ZIP Code : Pratt, Ks. 67124 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL... 118 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL .. 45 ft. below land surface measured on mo/day/yr 2-17-00
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield .. na gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter. 7 in. to 118 1/2 ft., and in. to ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes.....No.....x.....; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes x No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued .. x .. Clamped ..
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded ..
 2 PVC 4 ABS 7 Fiberglass Threaded ..
 Blank casing diameter 3 1/2 in. to 113 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface. 24 in., weight SDR 26 lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) ..
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ..
 SCREEN-PERFORATED INTERVALS: From 113 ft. to 118 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 118 1/2 ft. to 20 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug
 Grout Intervals: From 20 ft. to 0 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage none
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top soil			
3	13	Sand and gravel dirty dark colored			
13	26	Brown & white clay			
26	32	Yellow brown sandy clay			
32	45	Sand & gravel clean, coarse, loose			
45	63	Reddish brown clay			
63	90 1/2	Sand & gravel clean, coarse, loose			
90 1/2	96	Brown & white clay			
96	118	Sand & gravel clean, coarse, loose			
118	118 1/2	Gray clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-17-00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 2-22-00 under the business name of Rosencrantz-Bemis by (signature) Freddie Dodson

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4