

Main well

1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 NE 1/4 Section Number 11 Township Number T 27 S Range Number R 12 XEW
County: Pratt
Distance and direction from nearest town or city street address of well if located within city? 3 south, 2 1/2 west of Preston, Ks.

2 WATER WELL OWNER: Ramblin Rose Ranch
RR#, St. Address, Box #: 60176 NE 15th St.
City, State, ZIP Code: Pratt, Ks. 67124
Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NE section]
4 DEPTH OF COMPLETED WELL: 91 1/2 ft. ELEVATION:
Depth(s) Groundwater Encountered: 1 ft. 2 ft. 3 ft.
WELL'S STATIC WATER LEVEL: 62 ft. below land surface measured on mo/day/yr 7-20-00
Pump test data: Well water was ... ft. after ... hours pumping ... gpm
Est. Yield: NA gpm: Well water was ... ft. after ... hours pumping ... gpm
Bore Hole Diameter: 5 1/2 in. to 9 1/2 ft., and ... in. to ... ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well observation
Was a chemical/bacteriological sample submitted to Department? Yes. X No. ...; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. X Clamped.
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
7 Fiberglass Threaded
Blank casing diameter: 2 1/2 in. to 86 ft., Dia. in. to ... ft., Dia. in. to ... ft.
Casing height above land surface: 24 in., weight SDR26 lbs./ft. Wall thickness or gauge No. ...

TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify) ... ft.
SCREEN-PERFORATED INTERVALS: From 86 ft. to 91 ft., From ... ft. to ... ft.
GRAVEL PACK INTERVALS: From 91 1/2 ft. to 20 ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug
Grout Intervals: From 20 ft. to 0 ft., From ... ft. to ... ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage none
Direction from well? How many feet?

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0-3 Top soil, 3-14 Brown & white clay, 14-35 Sand & gravel clean, coarse, loose, 35-37 Brown clay, 37-45 Sand & gravel clean, coarse, loose, 45-48 Brown clay, 48-60 Sand & gravel clean, coarse, loose, 60-63 Sand & clay mixed, 63-91 1/2 Sand & gravel clean, coarse, loose, 91 1/2 Brown clay.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-20-00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 134 This Water Well Record was completed on (mo/day/yr) 7-26-00 under the business name of Rosencrantz-Bemis by (signature) Lara Aley