

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: PRATT		SW 1/4 SE 1/4 SW 1/4	34	T 27 S	R 13 EW
Distance and direction from nearest town or city street address of well if located within city? 516 E 1ST VE3					
2 WATER WELL OWNER: JAYS GG RR#, St. Address, Box #: 516 E 1ST City, State, ZIP Code: PRATT KS 67124 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 46 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 42 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 42 ft. below land surface measured on mo/day/yr 1/30/96			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to 47 ft., and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering ⑫ Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well SULLY VENT			
Was a chemical/bacteriological sample submitted to Department? Yes.....No X If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped ② PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X					
Blank casing diameter 2 in. to 36 ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. SC 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped ⑧ Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 36 ft. to 46 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 35 ft. to 46 ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement ② Cement grout ③ Bentonite 4 Other Grout Intervals: From 22 ft. to 0 ft., From 35 ft. to 22 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy ⑩ Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon ⑪ Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? N How many feet? 50					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4"	CEMENT			
4"	1	FILL SAND			
1	4	SANDY CLAY, RED-BRN			
4	9	SANDY SILT, RED-ORG			
9	11	FOR-MGR SILTY SAND			
11	13	SANDY SILT			
13	14	BRN SANDY SILT GRAY TO GRAY			
19	24	GRAY SANDY CLAY & SILT			
24	26	SANDY SILT, RED			
26	29	GRAY SANDY SILT			
29	47	SAND AND SILT			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/30/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 6-14-96 under the business name of ACD SERVICES INC by (signature) <i>Richard Resner</i>					