


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>PRATT</u>	<u>SE 1/4 SE 1/4 NW 1/4</u>	<u>03</u>	T <u>27</u> S	R <u>13</u> EW

Distance and direction from nearest town or city street address of well if located within city?

MAIN & SUMNER LUKA, KS

2 WATER WELL OWNER: <u>LUKA COOP</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>Box 175</u>	Application Number:
City, State, ZIP Code: <u>LUKA, KS 67064</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>55</u> ft. ELEVATION: <u>1942.40</u>
	Depth(s) Groundwater Encountered <u>1 47.94</u> ft. 2. <u>~48'</u> ft. 3. <u>5/3/00</u> ft.
	WELL'S STATIC WATER LEVEL <u>47.94</u> ft. below land surface measured on mo/day/yr
	Pump test data: Well water was <u>10.25</u> in. to <u>55</u> ft. after <u>5/3/00</u> hours pumping
	Est. Yield <u>10.25</u> gpm: Well water was <u>55</u> ft. after <u>5/3/00</u> hours pumping
	Bore Hole Diameter <u>10.25</u> in. to <u>55</u> ft. and <u>55</u> in. to <u>55</u> ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>VAPOR EXTRACTION</u>
	Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes <u>No</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>Clamped</u>
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter <u>4</u> in. to <u>40</u> ft., Dia			11 Other (specify)
Casing height above land surface <u>25.32</u> in., weight <u>55</u> lbs./ft. Wall thickness or gauge No. <u>SCH 40</u>			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)
SCREEN OR PERFORATION OPENINGS ARE:			10 Asbestos-cement
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	11 Other (specify)
2 Louvered shutter	4 Key punched	6 Wire wrapped	12 None used (open hole)
SCREEN-PERFORATED INTERVALS:			
From <u>40</u> ft. to <u>55</u> ft.			
From <u>37</u> ft. to <u>55</u> ft.			
GRAVEL PACK INTERVALS:			
From <u>37</u> ft. to <u>55</u> ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>3</u> ft. to <u>33</u> ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well?				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	CLAY			
8	10	SAND			
10	23	CLAY			
23	48	SILT			
48	50	SAND			
50	55	SILT			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>04/13/2000</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>594</u> This Water Well Record was completed on (mo/day/yr) <u>04/10/2000</u> under the business name of <u>ORMAC GREAT PLAINS</u> by (signature) <u>[Signature]</u>
