

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Pratt	SW 1/4 SW 1/4 SW 1/4	33	T 27 S	R 13 W 6W

Distance and direction from nearest town or city street address of well if located within city?

1 mile west of Pratt, Kans

2 WATER WELL OWNER: Pratt Humane Society	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : 418 North High	Application Number:
City, State, ZIP Code : Pratt, Kansas 67124	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 95' ft. ELEVATION: 42' ft.
	Depth(s) Groundwater Encountered 1. 42' ft. 2. 42' ft. 3. 42' ft.
	WELL'S STATIC WATER LEVEL 42' ft. below land surface measured on mo/day/yr
	Pump test data: Well water was NA ft. after NA hours pumping NA gpm
	Est. Yield NA gpm: Well water was NA ft. after NA hours pumping NA gpm
	Bore Hole Diameter 8 1/4" in. to 95' ft., and 95' ft. to 95' ft.
WELL WATER TO BE USED AS:	
☒ 1 Domestic ☐ 2 Irrigation ☐ 3 Feedlot ☐ 4 Industrial ☐ 5 Public water supply ☐ 6 Oil field water supply ☐ 7 Lawn and garden only ☐ 8 Air conditioning ☐ 9 Dewatering ☐ 10 Monitoring well ☐ 11 Injection well ☐ 12 Other (Specify below)	
Was a chemical/bacteriological sample submitted to Department? Yes XX No XX ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes ZZ No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued XX Clamped
1 Steel	3 RMP (SR)	9 Other (specify below)	Welded
2 PVC XX	4 ABS	7 Fiberglass	Threaded
Blank casing diameter 5 in. to 82' ft., Dia 82' in. to 82' ft., Dia 82' in. to 82' ft.			
Casing height above land surface 14" in., weight 160 lbs./ft. Wall thickness or gauge No. Sdr 26			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC XX	10 Asbestos-cement
1 Steel	3 Stainless steel	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	XX 8 Saw cut
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 82' ft. to 95' ft., From 82' ft. to 95' ft., From 82' ft. to 95' ft.			
GRAVEL PACK INTERVALS: From 95' ft. to 15' ft., From 95' ft. to 15' ft., From 95' ft. to 15' ft.			

6 GROUT MATERIAL: xx 1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 95' ft. to 15' ft., From 95' ft. to 15' ft., From 95' ft. to 15' ft.			
What is the nearest source of possible contamination:		10 Livestock pens	14 Abandoned water well
XX 1 Septic tank	4 Lateral lines	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	13 Insecticide storage	
Direction from well? South		9 Feedyard	How many feet? 125'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	7'	top soil			
7'	19'	sandy clay			
19'	27'	Brn. clay			
27'	43'	fine sand.			
43'	51'	sandy clay.			
51'	72'	Silty clay.			
72'	95'	Course sand.			
95'		Red bed.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Dec. 21 89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 112 This Water Well Record was completed on (mo/day/yr) Mar 12 1990 under the business name of Wells Drilling Co. by (signature) Deal Wells
--