USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	County	Fraction		Section number		Township number	Range number		
	Pratt	SE 1/4 SE 1/4 NE	1/4	3	6	т 2 <b>7</b> s	R 13	<b>₽</b> €₩)	
Distance and direction from nearest town or city:					l: ,	John Dauner			
2 miles East of Pratt, KS Street address of well location if in city:				•		Star Route			
City, state					code: ]	Pratt, KS 67124  6. Bore hole dia. 5 in. Completion date 7-12-77			
4. Locate with "X" in section below:  Sketch map:						6. Bore hole dia. 5 in.  Well depth 102 ft.	. Completion date 🚣	-12-77	
					ŀ	7 Cable tool Rotary Driven Dug			
						Hollow rod Jetted Bored X_Reverse rotary			
X   X   E						8. Use: Domestic Public supply Industry Irrigation Air conditioning X Stock			
									LawnOil field waterOther 9. Casing: Material Galv. Height: (Above) or below
						ALSO			
	RMP PVC Weight I lbs./ft.  Dia. 2 in. to 84 ft. depth Wall Thickness: inches or								
1 Mile ————————————————————————————————————					tic	Dia. 2 in. to 84 ft. depth Wall Thickness, inches or Dia. 2 in. to 92 ft. depth gage No. 180#			
5. Type and color of material				From	То	10. Screen: Manufacturer's n	Peerle	ess	
							Prasti	cs	
Top soil & sand & gravel				0	8	Type PVC 160	_ Dia2''		
Limestone & clay				8	16	Slot gauze <u>1/8</u> Set between <u>92</u>	_ Length102 _ftand102		
and f anaval			16	36	ft. andft.				
sand & gravel						Gravel pack? <u>Ye</u> Ssize range of material 3/8-200			
Clay				36	38	11. Static water level: mo./day/yr			
Sand & gravel & thin clay streaks				38	59	12. Pumping level below land surfaces: N/C			
Clay				59	61	ft. after hrs. pumping g.p.m g.p.m g.p.m.			
· · · · · · · · · · · · · · · · · · ·				61	74	Estimated maximum yieldg.p.m.			
Sand & gravel				61	74	13. Water sample submitted: mo./day/yr.			
Clay				74	76	Yes X No Date  14. Well head completion:			
Sand & gravel				76	102	Pitless adapter			
8-1-1-1				<del>                                     </del>		15. Well grouted? <u>YCS</u> With: X Negt cement Bentonite Concrete			
						Depth: From Off. to 10 ft.			
						16. Nearest source of possible contamination: Field			
						ft Direction Type Well disinfected upon completion? Yes No			
						17. Pump:	Not installed ayton Mark	& CO 2	
						Manufacturer's name	HP Vol	1 / 1 / 1 / 1 / 1 / 1 / 1 / 1 / 1 / 1 /	
						Length of drop pipe 841	_ ft. capacity ==_	-g.p.m. 🔊	
						Type: 211 x 1011 bi	rass cylind	ler	
				1		Jet	Turbine		
(Use a second sheet if needed)						Centrifugal	Other	Sec	
18. Elevation: 19. Remarks:						20. Water well contractor's a		10	
						This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Topography:						Clarke Well & Eq., Inc. 185			
HillSlope						Business name Great Bend	d, KS 6753	ense No.	
Upland					,	Signed Signed	Z) ota	15-77 N	
Valley						Authorized repr	esentative		