WATER WELL RECORD Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: Fraction	Section Number Township No. Range Number
County: PRATT NE ¼ SE ¼ NE ¼ NW ½	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here .	Global Positioning System (GPS) information: Latitude: .37.64395
•	Longitude: 98.73087 (in decimal degrees)
602 EAST 1ST, PRATT, KS 67124	Elevation: 1863.87
2 WATER WELL OWNER: KDHF-BFR	<u>Datum</u> : WGS 84, NAD 83, NAD 27
2 WATER WELL OWNER: KDHE-BER RR#, Street Address, Box #: 1000 SW JACKSON ST.,STE.#410	Collection Method: GPS unit (Make/Model:)
City, State, ZIP Code : TOPEKA, KS 66612-1367	☐ Digital Map/Photo, ☐ Topographic Map, ☑ Land Survey
	Est. Accuracy:
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 40.0	
SECTION BOX: Depth(s) Groundwater Encountered (1).~29.0.	ft. (2) ft. (3) ft.
N WELL'S STATIC WATER LEVEL. 29.45f	ft. (2) ft. (3) ft. t. below land surface measured on mo/day/yr
	ft. after hours pumping gpm
	ft. after hours pumping gpm
W Bore Hole Diameterin. toft., andin. toft. WELL WATER TO BE USED AS: Public water supply Geothermal Injection well	
ow or Domestic Feedlot Oil field was	ter supply Dewatering Other (Specify below)
│	wn & garden Monitoring well MW35
Was a chemical/bacteriological sample submitted t	o Department? Yes V No
S If yes, mo/day/yr sample was submitted Water well disinfected? Yes No	
5 TYPE OF CASING USED: Steel PVC Other	
Casing diameter .2 in. to .25.0 ft., Diameter ft., Diameter ft.	
Casing height above land surface6.60 in., Weight	lbs./ft., Wall thickness or gauge NoSch. 40.P.Y.C
TYPE OF SCREEN OR PERFORATION MATERIAL:	
Steel Stainless Steel PVC Other (Specify)	
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:	
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)	
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From	
	ft., From ft. to ft. ft. ft. ft. ft. ft. ft. ft. f
GRAVEL PACK INTERVALS: From 23 ft. to .40	ft. From ft to ft
From ft. to	ft., From ft. to ft.
6 GROUT MATERIAL: Neat cement Cement grout Bento	onite \square Other
Grout Intervals: From .1	. ft. to ft., From ft. to ft.
What is the nearest source of possible contamination: ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock	pens Insecticide storage Other (specify below)
Sewer lines Cesspool Sewage lagoon Fuel store	ge
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer	
	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
FROM TO LITHOLOGIC LOG FROM 1 TOPSOIL	LITTO, LOG (COIII.) OI PLOGGING INTERVALS
1 7 CLAY, SILTY	
7 7.5 SAND&GRAVEL 1/8", FINE TO COARSE	
7.5 14 SAND, FINE TO COARSE	
14 26 CLAY, SANDY	MW35
26 40 SAND, FINE TO MEDIUM	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This wa	iter well was 🗸 constructed, 🗌 reconstructed, or 🗌 plugged
under my jurisdiction and was completed on (mo/day/year) .09/30/2014 and this record is true to the best of my knowledge and belief.	
Kansas Water Well Contractor's License No. 594 This Water Well	
under the business name ofCORANGO Great Plains, Inc	
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.	
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.	
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy	