

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: PRATT		NW ¼ SE ¼ NW ¼		22		T 27 S		R 14 E/W			
Distance and direction from nearest town or city street address of well if located within city? 5-W 2-N. OF PRATT, KS.											
2 WATER WELL OWNER: WHITE & ELLIS DRILLING INC.					Dimension 1						
RR#, St. Address, Box #: P.O. BOX 1586					Board of Agriculture, Division of Water Resources						
City, State, ZIP Code: Great Bend, KS 67530					Application Number: 93-0297						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 153 ft. ELEVATION:								
			Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.								
			WELL'S STATIC WATER LEVEL: 56 ft. below land surface measured on mo/day/yr								
			Pump test data: Well water was ft. after hours pumping gpm								
			Est. Yield gpm: Well water was ft. after hours pumping gpm								
			Bore Hole Diameter: .9 in. to ft., and in. to ft.								
WELL WATER TO BE USED AS:			5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot ☒ Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well								
Was a chemical/bacteriological sample submitted to Department? Yes.....No... ☒			If yes, mo/day/yr sample was submitted								
Water Well Disinfected? Yes No ☒											
5 TYPE OF BLANK CASING USED:											
1 Steel			3 RMP (SR)			5 Wrought iron			8 Concrete tile		
☒ PVC			4 ABS			6 Asbestos-Cement			9 Other (specify below)		
Blank casing diameter: 5 in. to 143 ft., Dia			in. to ft., Dia			Casing joints: Glued ☒ Clamped			Welded		
Casing height above land surface: 18 in., weight			lbs./ft. Wall thickness or gauge No.			Threaded					
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel			3 Stainless steel			5 Fiberglass			☒ PVC		
2 Brass			4 Galvanized steel			6 Concrete tile			8 RMP (SR)		
SCREEN OR PERFORATION OPENINGS ARE:			5 Gauzed wrapped			8 Saw cut			11 None (open hole)		
1 Continuous slot			☒ Mill slot			6 Wire wrapped			9 Drilled holes		
2 Louvered shutter			4 Key punched			7 Torch cut			10 Other (specify)		
SCREEN-PERFORATED INTERVALS:											
From: 143 ft. to 153 ft., From			ft. to ft., From			ft. to ft., From			ft. to ft., From		
GRAVEL PACK INTERVALS:											
From: 20 ft. to 153 ft., From			ft. to ft., From			ft. to ft., From			ft. to ft., From		
6 GROUT MATERIAL:											
1 Neat cement			2 Cement grout			☒ Bentonite			4 Other		
Grout Intervals: From: 0 ft. to 20 ft., From											
What is the nearest source of possible contamination:											
1 Septic tank			4 Lateral lines			7 Pit privy			10 Livestock pens		
2 Sewer lines			5 Cess pool			8 Sewage lagoon			11 Fuel storage		
3 Watertight sewer lines			6 Seepage pit			9 Feedyard			12 Fertilizer storage		
									13 Insecticide storage		
									14 Abandoned water well		
									15 Oil well/Gas well		
									16 Other (specify below)		
									NONE KNOWN		
Direction from well? How many feet?											
LITHOLOGIC LOG											
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS					
0	3	TOP SOIL									
3	90	CLAY									
90	135	SAND & CLAY									
135	153	GRAVEL									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) AUGUST 25, 1993 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 462-B This Water Well Record was completed on (mo/day/year) OCT 19, 1993 under the business name of SAM'S WATER WELL SERVICE by (signature) <i>Lora R. Ruffin</i>											
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.											

OFFICE USE ONLY

T

R

E/W

SEC.

1/4

1/4

1/4