

## CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

County: Pratt

Location listed as:

Location ~~changed to~~:

Section-Township-Range: \_\_\_\_\_

5-27 S-15WFraction (  $\frac{1}{4}$   $\frac{1}{4}$   $\frac{1}{4}$ ): \_\_\_\_\_NE NE SWOther changes: Initial statements: Well water to be used as: DomesticChanged to: Monitoring

Comments: \_\_\_\_\_

verification method: Personal communication from Brownie Wilson(KGS' Hydro. Dept. data & web manager)initials: DRK date: 4/18/2011

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726

to: Kansas Dept of Health &amp; Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number  
 COUNTY: 076 PRATT NE 1/4 NE 1/4 SW 1/4 5 T 27 S R 15 W

Distance and direction from nearest town or city street address of well if located within city?  
 6 N. 5 W. OF CULLISON

2 WATER WELL OWNER: G.W.M.D. # 5 352  
 RR#, St. Address, Box #: P.O. BOX 5 Board of Agriculture, Division of Water Resources

City, State, ZIP code : STAFFORD, KS 67578- Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX *Well #4*

1	NW	NE
W	X	E
SW	SE	

4 DEPTH OF COMPLETED WELL 137 ELEVATION: 0  
 Depth(s) Groundwater Encountered 1. 46 ft. 2. 0 ft. 3. 0 ft.

WELL'S STATIC WATER LEVEL 46 ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm  
 Estimated Yield 0 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm  
 Bore Hole Diameter 7.75 in. to 137 ft., and in. to 0 ft.  
 WELL WATER TO BE USED AS: 01 DOMESTIC  
 Was a chemical/bacteriological sample submitted to department? No ;  
 If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: 02 PVC CASING JOINTS: GLUED  
 Blank casing diameter 4 in. to 127 ft., Dia in. to 0 ft., Dia in. to 0 ft.  
 Casing height above land surface 12 in., weight 0 lbs/ft. Wall thickness or gauge No. 26  
 TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC  
 SCREEN OR PERFORATION OPENINGS ARE: 08 SAW CUT

SCREEN PERFORATED INTERVALS: From 127 ft. to 137 ft., From 0 ft. to 0 ft.  
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.  
 GRAVEL PACK INTERVALS: From 137 ft. to 120 ft., From 0 ft. to 0 ft.  
 From 100 ft. to 24 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL 03 BENTONITE  
 Grout Intervals: From 120 ft. to 100 ft., From 24 ft. to 3 ft., From 0 ft. to 0 ft.  
 What is the nearest source of possible contamination: CATTLE PASTURE  
 Direction from well? ALL How many feet? 3

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	14	SILT & SAND			
14	39	TAN CLAY			
39	50	05 SAND AND 17 GRAVEL			
50	62	TAN CLAY			
62	108	05 SAND AND 17 GRAVEL			
108	118	TAN CLAY			
118	137	05 SAND AND 17 GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) *3 / 1 / 96* and this record is true to the best of my knowledge and belief. Kansas  
 Water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/yr) 03/08/96  
 under the business name of CARL HAYSE WATER WELL SVC by (signature) *Carl Hayse*