

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

County: Pratt

Location listed as:

Location ~~changed to~~:

Section-Township-Range: _____

5-27 S-15 WFraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): _____SW NE SWOther changes: Initial statements: Well water to be used as: DomesticChanged to: Monitoring

Comments: _____

verification method: Personal communication from Brownie Wilson
(KGS' Hydro. Dept. data & web manager)initials: ORA date: 4/18/2011submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 COUNTY: 076 PRATT SW 1/4 NE 1/4 SW 1/4 5 T 27 S R 15 W

Distance and direction from nearest town or city street address of well if located within city?
 6 N. 5 W. OF CULLISON, KS

2 WATER WELL OWNER: G.W.M.D.#5 351
 RR#, St. Address, Box #: P.O. BOX 7 Board of Agriculture, Division of Water Resources

City, State, ZIP code : STAFFORD, KS 67578- Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Well #, 4 DEPTH OF COMPLETED WELL 90 ELEVATION: 0
 Depth(s) Groundwater Encountered 1. 35 ft. 2. 0 ft. 3. 0 ft.
 WELL'S STATIC WATER LEVEL 35 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm
 Estimated Yield 0 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm
 Bore Hole Diameter 7.75 in. to 90 ft., and in. to 0 ft.
 WELL WATER TO BE USED AS: 01 DOMESTIC
 Was a chemical/bacteriological sample submitted to department? No ;
 If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: 02 PVC CASING JOINTS: GLUED
 Blank casing diameter 4 in. to 80 ft., Dia in. to 0 ft., Dia in. to 0 ft.
 Casing height above land surface 12 in., weight 0 lbs/ft. Wall thickness or gauge No. 26
 TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC
 SCREEN OR PERFORATION OPENINGS ARE: 08 SAW CUT

SCREEN PERFORATED INTERVALS: From 80 ft. to 90 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 GRAVEL PACK INTERVALS: From 90 ft. to 25 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL 03 BENTONITE
 Grout Intervals: From 25 ft. to 4 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 What is the nearest source of possible contamination: CATTLE PASTURE
 Direction from well? ALL How many feet? 3

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	SILT & SAND			
4	26	TAN CLAY			
26	38	05 SAND AND 17 GRAVEL			
38	54	TAN CLAY			
54	90	05 SAND AND 17 GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 3-1-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/yr) 03/08/96 under the business name of CARL HAYSE WATER WELL SVC by (signature) Carl Hayse