

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

County: Pratt

Location listed as:

Location ~~changed to~~:

Section-Township-Range: _____

5-27 S-15 WFraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): _____SE NW SWOther changes: Initial statements: Well water to be used as: DomesticChanged to: Monitoring

Comments: _____

verification method: Personal communication from Brownie Wilson
(KGS' Hydro. Dept. data & web manager)initials: ORA date: 4/18/2011submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 COUNTY: 076 PRATT SE 1/4 NW 1/4 SW 1/4 5 T 27 S R 15 W

Distance and direction from nearest town or city street address of well if located within city?
 6 N, 5 W OF CULLISON, KS.

2 WATER WELL OWNER: G.W.M.D. #5 348
 RR#, St. Address, Box #: P.O. BOX 7 Board of Agriculture, Division of Water Resources
 City, State, ZIP code: STAFFORD, KS 67578- Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX *Well #7*

1	NW	NE
M		
i		
l		
e	SW	SE

4 DEPTH OF COMPLETED WELL 130 ELEVATION: 0
 Depth(s) Groundwater Encountered 1. 40 ft. 2. 0 ft. 3. 0 ft.
 WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr 2 /28/96
 Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm
 Estimated Yield 0 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm
 Bore Hole Diameter 7.75 in. to 130 ft., and in. to 0 ft.
 WELL WATER TO BE USED AS: 01 DOMESTIC
 Was a chemical/bacteriological sample submitted to department? No ;
 If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: 02 PVC CASING JOINTS: GLUED
 Blank casing diameter 4 in. to 120 ft., Dia in. to 0 ft., Dia in. to 0 ft.
 Casing height above land surface 12 in., weight 0 lbs/ft. Wall thickness or gauge No. 26
 TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC
 SCREEN OR PERFORATION OPENINGS ARE: 08 SAW CUT

SCREEN PERFORATED INTERVALS: From 120 ft. to 130 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 GRAVEL PACK INTERVALS: From 130 ft. to 114 ft., From 0 ft. to 0 ft.
 From 100 ft. to 22 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL 03 BENTONITE
 Grout Intervals: From 114 ft. to 100 ft., From 22 ft. to 2 ft., From 0 ft. to 0 ft.
 What is the nearest source of possible contamination: CATTLE PASTURE
 Direction from well? ALL How many feet? 3

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	SILT & SAND			
8	32	TAN CLAY			
32	41	05 SAND AND 17 GRAVEL			
41	55	TAN CLAY			
55	92	05 SAND AND 17 GRAVEL			
92	93	TAN CLAY			
93	101	05 SAND AND 17 GRAVEL			
101	113	TAN CLAY			
113	130	05 SAND AND 17 GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) *2-28-96* and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/yr) 03/08/96
 under the business name of CARL HAYSE WATER WELL SVC by (signature) *Carl Hayse*